

Sensor - PIR Ceiling Mount OCC/VAC Sensor

Item ALC-CMP-BT



PRODUCT DESCRIPTION

The ALC-CMP-BT is a Passive Infrared Sensor designed for use with the ARISTA® Lighting Controls System by Intermatic and will control lighting based upon occupancy/vacancy. If the space is configured for Occupancy and movement is detected, the sensor informs the ARISTA controller(s) in the space and the lights will illuminate. The lights will turn off after the ARISTA controller(s) deem the space vacant and the timeout period completes. If the space is configured for Vacancy, the ARISTA controller(s) in the space will only react when they are manually activated. The lights will turn off after the ALC-CMP-BT deems the space vacant and the timeout period completes. This sensor provides a 360° coverage pattern, up to 1200 ft². Pricing Available Upon Request.

FEATURES

- ▶ Battery or 24 VDC powered
- ▶ Wired or wireless communications
- ▶ Toolless battery replacement
- ▶ Multiple mounting options
- ▶ Adjustable sensitivity settings
- ▶ Adjustable time-out settings

APPLICATIONS

- ▶ Indoor Lighting Control
- ▶ Indoor Sensing Control

TECHNICAL DATA

General	
Model Number	ALC-CMP-BT
Description	PIR Ceiling Mount OCC/VAC Sensor
UPC Code	078275150713
Brand	Intermatic
Warranty Period	5-Year limited
Country of Origin (Intermatic)	CHINA

Control Specifications	
Operation Features	Presence
Operation Mode	Occupancy; Vacancy
Data Transfer Options	Bluetooth
Backup Restoration Time	1 Minute
Backup Type	Non-volatile
Backup Protection Time	Indefinite
PIR Coverage Area (sq ft)	1200
Application Compatibilities	ARISTA Controllers
Function type	Occupancy; Scheduled ON/OFF; Vacancy

Mechanical Specifications	
Mount Type	Ceiling

Dimensions	
Product Height (in)	4.53
Product Height (mm)	115.062

Product Width (in)	4.53
Product Width (mm)	115.062
Product Depth (in)	2.95
Product Depth (mm)	74.93
Class 2 Wire Size Min	22
Class 2 Wire Size Max	16

Communication Method

Radio signal	Bluetooth
--------------	-----------

Electrical Specifications

Voltage Selection Type	Selector Switch
Input Voltage Range(s)	3 V Battery, 24 VDC
Wiring Options Low Voltage	Terminals

Display and Format

Status Indicator	LED Indicator
------------------	---------------

Packaging

Product Weight (kg)	0.247
Product Weight (lbs)	0.546

Operating Specifications

Programming Targets	Smartphone
Tampering protection	Yes

Environmental Specifications

Operating Humidity	Dry Location
Temperature (operation)	32°F..104°F
Temperature (operation)	0°C..40°C
Usage Environments	Indoor

Standards and Certifications

UL Certification	cULus
Other Certifications and Compatibilities	Ashrae 90.1 2016; IECC 2018; Title 20
California Proposition 65	None
RoHS Certification	Yes