


In-Wall Timer - Electronic Countdown Timer, 120 VAC, 60 Hz, Preset Times 5,10,15,30 Minute, With Hold, Light Almond

Item EI200LA



PRODUCT DESCRIPTION

This timer requires no programming; preset countdown times are activated by pressing a single button. Silent operation makes this timer ideal for applications where the noise of mechanical countdown timers is of concern. *NOTE: Not for use with sunlamps, saunas, or loads that could cause personal injury if timed incorrectly.

FEATURES

- ▶ No programming required
- ▶ Provides silent operation in time ranges from five minutes to 30 minutes
- ▶ Single-button time selection, with some models having a HOLD mode, for continuous ON operation
- ▶ Replaces single-pole switches in a variety of applications
- ▶ Incandescent/fluorescent/CFL/LED compatible
- ▶ For use with decorator-style wall plate (not included)
- ▶ Requires neutral connection

APPLICATIONS

- ▶ Indoor Lighting Control
- ▶ Air Movement & Ventilation

TECHNICAL DATA

General	
Model Number	EI200LA
Description	Electronic Countdown Timer, 120 VAC, 60 Hz, Preset Times 5,10,15,30 Minute, With Hold, Light Almond
UPC Code	078275100572
Brand	Intermatic
Country of Origin (Intermatic)	CHINA
Warranty Period	1-Year limited
Control Specifications	
Time Presets	5 min; 10 min; 15 min; 30 min
Setpoint Program Count	4
Operation Mode	Countdown
Countdown Time	30 min
Hold Mode Included	Yes
Mechanism Type	Digital/Electrical
Application Compatibilities	Incandescent; Fluorescent; CFL; LED
Mechanical Specifications	
Wall Plate Configurations	Single-Gang
Dimensions	
Product Dimensions (H x W x D) in	4.125 x 1.688 x 1.438 in
Material Specifications	
Color	Light Almond

Load Ratings		
Resistive Heater		15 A, 1800 W
Tungsten (Incandescent) Range(s)		1000 W
Ballast Fluorescent		8 A, 1000 VA
Electronic Ballast LED		4 A, 500 VA
Motor Load Ratings Ranges		1/4 HP

Electrical Specifications		
Input Voltage Range(s)		120 VAC, 60 Hz
Wiring Configurations		Single
Neutral Connection Required		Yes

Environmental Specifications		
Temperature (operation)		32 - 104 °F / 0 - 40 °C

Packaging		
Unit Carton Dimensions (H x W x D) in		4.88 x 3 x 2.13 in

Standards and Certifications		
UL Certification		cULus
California Proposition 65		DEHP
RoHS Certification		Yes