

**In-Wall Timer** - Electronic Countdown Timer, 120 VAC, 60 Hz, Preset Times 1,2,4,8 Hour, With Hold, White

Item EI220W



**PRODUCT DESCRIPTION**

This timer requires no programming; preset countdown times are activated by pressing a single button. Silent operation makes this timer ideal for applications where the noise of mechanical countdown timers is of concern. \*NOTE: Not for use with sunlamps, saunas, or loads that could cause personal injury if timed incorrectly.

**FEATURES**

- ▶ No programming required
- ▶ Provides silent operation in time ranges from One hour to 8 hours
- ▶ Single-button time selection, with some models having a HOLD mode, for continuous ON operation
- ▶ Replaces single-pole switches in a variety of applications
- ▶ Incandescent/fluorescent/CFL/LED compatible
- ▶ For use with decorator-style wall plate (not included)
- ▶ Requires neutral connection

**APPLICATIONS**

- ▶ Indoor Lighting Control
- ▶ Air Movement & Ventilation

**TECHNICAL DATA**

General	
Model Number	EI220W
Description	Electronic Countdown Timer, 120 VAC, 60 Hz, Preset Times 1,2,4,8 Hour, With Hold, White
UPC Code	078275095274
Brand	Intermatic
Country of Origin (Intermatic)	CHINA
Warranty Period	1-Year limited
Control Specifications	
Time Presets	1 hr; 2 hrs; 4 hrs; 8 hrs
Setpoint Program Count	4
Operation Mode	Countdown
Countdown Time	8 hrs
Hold Mode Included	Yes
Mechanism Type	Digital/Electrical
Application Compatibilities	Incandescent; Fluorescent; CFL; LED
Mechanical Specifications	
Wall Plate Configurations	Single-Gang
Dimensions	
Product Dimensions (H x W x D) in	4.125 x 1.688 x 1.438 in
Material Specifications	
Color	White

Load Ratings		
General Purpose		15 A, 120 VAC, 60 Hz
Resistive Heater		15 A, 1800 W
Tungsten (Incandescent) Range(s)		1000 W
Ballast Fluorescent		8 A, 1000 VA
Electronic Ballast LED		4 A, 500 VA
Motor Load Ratings Ranges		1/4 HP

Electrical Specifications		
Input Voltage Range(s)		120 VAC, 60 Hz
Wiring Configurations		Single
Neutral Connection Required		Yes

Environmental Specifications		
Temperature (operation)		32 - 104 °F / 0 - 40 °C

Packaging		
Unit Carton Dimensions (H x W x D) in		4.88 x 3 x 2.13 in

Standards and Certifications		
UL Certification		cULus
California Proposition 65		DEHP
RoHS Certification		Yes