

Occupancy Sensor - Commercial Grade In-Wall 0-10 V Dimming PIR Occupancy/Vacancy Sensor, White

Item IOS-DOV-D-WH



PRODUCT DESCRIPTION

Intermatic's IOS-DOV-D-WH PIR technology 0-10 V dimming occupancy sensor can turn lights ON and OFF based on occupancy and allow the user to increase or decrease the lighting level.

FEATURES

- ► Passive Infrared (PIR) sensing for presence detection
- ► Coverage: 180°, up to 35 ft PIR
- ► Adjustable time delay
- Adjustable initial on light level
- ► Adjustable low trim level
- ► Adjustable high trim level

APPLICATIONS

► Indoor Sensing Control

TECHNICAL DATA

General	
Model Number	IOS-DOV-D-WH
Description	Commercial Grade In-Wall 0-10 V Dimming PIR Occupancy/Vacancy Sensor, White
UPC Code	078275154001
Brand	Intermatic
Warranty Period	5-Year limited
Country of Origin (Intermatic)	TAIWAN

Control Specifications	
Sensor Switch Type	Occupancy; Vacancy
Sensor Technology	0 -10 Volt Dimming; PIR (Passive Infrared)
Adjustable Time Delay Min	30 sec
Adjustable Time Delay Max	30 min
Adjustable Light Level Max	Daylight
Has Walk-Through Detection	Yes
PIR Coverage Area (sq ft)	1120
Application Compatibilities	LED; Tungsten; Standard Ballast

Mechanical Specifications	
Mount Type	In-Wall
PIR Coverage Pattern (degrees)	35

Dimensions	
Product Height (in)	4.625
Product Height (mm)	117.475
Product Width (in)	3
Product Width (mm)	76.2
Product Depth (in)	2.19

Environmental Specifications

Temperature (operation)



Product Depth (mm)	55.626
Material Specifications	
Color	White
Includes Wall Plate	Yes
Load Ratings	
Tungsten Range(s)	1000 W, 120 VAC; 1385 W, 277 VAC
Resistive Load Ratings Ranges	10 A, 125/250/277 VAC
Motor Load Ratings Ranges	1/6 HP, 120/240 VAC
Electronic Ballast Load Ratings Ranges	600 VA, 120 VAC; 1385 W, 277 VAC
Electrical Specifications	
Input Voltage Range(s)	120/277 VAC, 50/60 Hz
Occupancy Sensor Power Type	Line Voltage
Number of Circuits	1
Neutral Connection Required	Yes
Packaging	
Shipping Weight (lbs)	0.307
Shipping Weight (kg)	0.139
Unit Carton Dimensions (H x W x L) in	4.625 x 3 x 2.19 in
Product Weight (lbs)	0.37

32 - 131°F / 0 - 55°C