

Occupancy Sensor - Commercial Grade Low-Voltage Power Pack Auto/Manual

Item IOS-PP25



PRODUCT DESCRIPTION

IOS-PP25 is a power pack with a 120 to 277 VAC, 50/60 Hz line voltage input. The power pack contains a full wave rectifier which can convert AC line voltage to 24 VDC to supply sensors with class 2 low voltage. Also, the power pack provides singlepole, single-throw, relay outputs to the load. The power pack is easily mounted either inside or outside of an electrical junction

FEATURES

- ► Auto (Occupancy)/Manual (Vacancy) toggle switch
- ► 24V/275 mA DC power output
- ► Single-pole and normally open relay
- Over current protection
- ► Relay contact protection

c(UL)us

APPLICATIONS

► Indoor Sensing Control

TECHNICAL DATA	
General	
Model Number	IOS-PP25
Description	Commercial Grade Low-Voltage Power Pack Auto/Manual
UPC Code	078275153950
Brand	Intermatic
Warranty Period	2-Year limited
Country of Origin (Intermatic)	TAIWAN
Control Specifications	
PIR Coverage Area (sq ft)	Depends on sensor being used
Application Compatibilities	Tungsten; Electronic Ballast; General Purpose; Standard Ballast
Mechanical Specifications	
Maximum Mounting Height (ft)	No maximum mounting height

Mechanical Specifications	
Maximum Mounting Height (ft)	No maximum mounting height

Dimensions	
Product Height (in)	3.544
Product Height (mm)	90.02
Product Width (in)	3.622
Product Width (mm)	92
Product Depth (in)	1.851
Product Depth (mm)	47.02

Material Specifications	
Color	Black

Load	Ratings

Tungsten Range(s) 15 A, 120 VAC Packaging



Motor Load Ratings Ranges	1 HP, 120 VAC
Electronic Ballast Load Ratings Ranges	16 A
General Purpose (NO) Range(s)	20 A
Standard Ballast Ranges	20 A

Electrical Specifications	
Input Voltage Range(s)	120-277 VAC, 50/60 Hz
Occupancy Sensor Power Type	Low Voltage

Power Connection	
Power Supply Output	Auto (Occupancy)/Manual (Vacancy) toggle switch

Unit Carton Dimensions (H x W x L) in	3.544 x 3.622 x 1.851 in
Environmental Specifications	
Temperature (operation)	32 - 104°F / 0 - 40°C

Standards and Certifications	
UL Certification	cULus
Other Certifications and Compatibilities	FCC
California Proposition 65	Lead; DEHP