

Photocontrol - Locking Type Thermal Photocontrol, 120-277 V

Item LC4536C



PRODUCT DESCRIPTION

These photocontrols install on light fixtures with ANSI C136.10 NEMA receptacles commonly found on street light fixtures. Locking type design facilitates fast installation and replacement of photocontrol.

FEATURES

- ▶ Mechanical bimetal switch with Cadmium Sulfide photocell
- ▶ Integral high impact thermoplastic housing
- ▶ Locking type plug for quick installation and changeover
- ▶ Delay feature prevents unwanted OFF switching
- ▶ Complies with ANSI C136.10 standard
- ▶ Tested to 3,650 ON/OFF cycles

APPLICATIONS

- ▶ Outdoor Lighting Control

TECHNICAL DATA

General

Model Number	LC4536C
Description	Locking Type Thermal Photocontrol, 120-277 V
UPC Code	078275029552
Brand	Intermatic
Country of Origin (Intermatic)	MEXICO
Warranty Period	2-Year limited

Control Specifications

Sensor Time Delay	30 sec to 90 sec
Photocell Type	Cadmium Sulfide
Photo Control Switch Type	Mechanical Bimetal
Fail Mode	ON
Activation On	5 fc
Activation Off	15 fc
Photocontrol Type	Thermal
Application Compatibilities	HID; Incandescent
Photocontrol Style	Locking type
Photocontrol Sensor Location	Side

Dimensions

Product Height (in)	2 3/4
Product Height (mm)	69.9
Product Diameter (in)	3
Product Diameter (mm)	76.2

Material Specifications

Cover Color	White with Blue Band
-------------	----------------------

Housing Material	Polypropylene
Load Ratings	
Magnetic Ballast Range(s)	8.3 A, 1000-2300 VA
Tungsten Range(s)	15 A, 1800-4155 W
Electrical Specifications	
Input Voltage Range(s)	120-277 VAC, 50/60 Hz
Packaging	
Unit Carton Dimensions (H x W x D) in	3.25 x 3.19 x 3.19 in
Operating Specifications	
Expected Lifetime (Years)	5
Expected Lifetime (Operations)	3650
Environmental Specifications	
Temperature (operation)	-40°C..70°C
Usage Environments	Outdoor
Standards and Certifications	
UL Certification	UL
CSA Certification	cCSAus
Other Certifications and Compatibilities	Title 20; Ansi C136.10
California Proposition 65	None

ACCESSORIES



K121
Locking Type Receptacle, 3-Pin, C136.10
Compliant, 9" lead



K121-30
Locking Type Receptacle, 3-Pin, C136.10
Compliant, 30" lead



K122
Locking Type Receptacle, 3-Pin, C136.10
Compliant, with Pole Mounting Bracket



K171H
Locking Type Receptacle, 7-Pin, C136.41
Compliant, 12" lead



KPT1170-010
PowerTap Receptacle, 7-Pin, C136.41
Compliant, Dusk-to-Dawn, 10' cable



KPT0170-010
PowerTap Receptacle, 7-Pin, C136.41
Compliant, Always-On, 10' cable



SK4500K
Shorting Plug for Locking Type Receptacles



KPT0170-015
PowerTap Receptacle, 7-Pin, C136.41
Compliant, Always-On, 15' cable



SK4500KMX
Shorting Plug for Locking Type Receptacles