

Electronic Timer Control - 24-Hour Electronic Time Control, 3-Circuit, Type 3R Metal Enclosure

Item PE153



PRODUCT DESCRIPTION

This multipurpose 24-hour control is capable of automatically switching loads according to a preset daily schedule. Controls single- and two-speed pumps and cleaner/booster pumps. Three ON/OFF events per circuit per day.

FEATURES

- ► Controls single- and two-speed pumps and cleaner/booster pumps
- ► Three ON/OFF events per circuit per day
- ► Seven preprogrammed modes
- ► Freeze and heater protection
- ► LCD readout
- ► Multivoltage input and output
- Countdown and override features enable programs to be overridden and automatically resumed without requiring the user to reprogram the system

APPLICATIONS

- ► Motor Control
- ► Pump Control

TECHNICAL DATA

(1)

General	
Model Number	PE153
Description	24-Hour Electronic Time Control, 3-Circuit, Type 3R Metal Enclosure
UPC Code	078275092358
Brand	Intermatic
Country of Origin (Intermatic)	CANADA
Warranty Period	1-Year limited
Control Specifications	
Maximum ON/OFF Operations	3
Operation Mode	24 hour
Mechanical Specifications	
Enclosure Type	Outdoor type 3R metal
Dimensions	
Product Dimensions (H x W x D) in	9.375 x 5.5 x 3.625 in
Load Ratings	
Tungsten Range(s)	5 A, 120/240 VAC, 50/60 Hz
	80 LRA @ 120 VAC, 50 Hz;80 LRA @ 240 VAC, 50 Hz;17 FLA @ 120 VAC, 50 Hz;17 FLA @ 24

FLA @ 240 VAC, 60 Hz

17 A, 120/240 VAC, 50/60 Hz

Electrical Specifications

Resistive Load Ratings Ranges

Motor Load Ratings Ranges

Motor

VAC, 50 Hz;80 LRA @ 120 VAC, 60 Hz;80 LRA @ 240 VAC, 60 Hz;17 FLA @ 120 VAC, 60 Hz;17

80 LRA @ 120/240 VAC, 50/60 Hz; 17 FLA @ 120/240 VAC, 50/60 Hz



Voltage Selection TypeMulti VoltageInput Voltage Range(s)120/240 VAC, 50/60 HzNumber of Circuits3Switch Type3-SPST

Packaging

Unit Carton Dimensions (H x W x L) in 4.251 x 7.251 x 11.501 in

Standards and Certifications		
CSA Certification	cCSAus	
California Proposition 65	DEHP	