

## Electronic Timer Control - 24-Hour Electronic Time Control, 3-Circuit, Freeze Protection Probe, Type 3R Plastic Enclosure

Item PE153PF



### PRODUCT DESCRIPTION

This multipurpose 24-hour control is capable of automatically switching loads according to a preset daily schedule. Controls single- and two-speed pumps and cleaner/booster pumps. Three ON/OFF events per circuit per day.

### FEATURES

- ▶ Controls single- and two-speed pumps and cleaner/booster pumps
- ▶ Three ON/OFF events per circuit per day
- ▶ Seven preprogrammed modes
- ▶ Freeze and heater protection
- ▶ LCD readout
- ▶ Multivoltage input and output
- ▶ Countdown and override features enable programs to be overridden and automatically resumed without requiring the user to reprogram the system

### APPLICATIONS

- ▶ Heater Thermostat Control
- ▶ Motor Control
- ▶ Pump Control

### TECHNICAL DATA

#### General

Model Number	PE153PF
Description	24-Hour Electronic Time Control, 3-Circuit, Freeze Protection Probe, Type 3R Plastic Enclosure
UPC Code	078275092402
Brand	Intermatic
Country of Origin (Intermatic)	CANADA
Warranty Period	1-Year limited

#### Control Specifications

Maximum ON/OFF Operations	3
Operation Mode	24 hour

#### Mechanical Specifications

Enclosure Type	Outdoor type 3R plastic
----------------	-------------------------

#### Dimensions

Product Dimensions (H x W x D) in	9.375 x 5.5 x 3.625 in
-----------------------------------	------------------------

#### Load Ratings

Tungsten Range(s)	5 A, 120/240 VAC, 50/60 Hz
Motor	80 LRA @ 120 VAC, 50 Hz; 80 LRA @ 240 VAC, 50 Hz; 17 FLA @ 120 VAC, 50 Hz; 17 FLA @ 240 VAC, 50 Hz; 80 LRA @ 120 VAC, 60 Hz; 80 LRA @ 240 VAC, 60 Hz; 17 FLA @ 120 VAC, 60 Hz; 17 FLA @ 240 VAC, 60 Hz
Resistive Load Ratings Ranges	17 A, 120/240 VAC, 50/60 Hz
Motor Load Ratings Ranges	80 LRA @ 120/240 VAC, 50/60 Hz; 17 FLA @ 120/240 VAC, 50/60 Hz

**Electrical Specifications**

Voltage Selection Type	Multi Voltage
Input Voltage Range(s)	120/240 VAC, 50/60 Hz
Number of Circuits	3
Switch Type	3-SPST

**Packaging**

Unit Carton Dimensions (H x W x L) in	5.501 x 12.001 x 13.751 in
---------------------------------------	----------------------------

**Standards and Certifications**

CSA Certification	cCSAus
California Proposition 65	DEHP