

Electronic Timer Control - 24-Hour 7-Day Electronic WiFi Time Control, 2-Circuit, Type 3R Plastic Enclosure

Item PE723P



PRODUCT DESCRIPTION

This general purpose 24-hour, 7-day timer control is capable of automatically switching loads according to a preset daily schedule. Simply wire to various downstream hard-wired pool equipment and turn these loads On and Off via schedule or manually through the Intermatic Connect Mobile App or Voice command.

FEATURES

- ▶ Schedule automatic ON/OFF operation of connected Pool equipment and make changes anywhere to suit your scheduled needs.
- ▶ Controls pool pumps, pool and spa lighting, landscape lighting, pool sanitation, and other auxiliary equipment
- ▶ Up to 96 ON/OFF events per day.
- ▶ Simple retrofit - knockout locations and sizes designed equivalently to Intermatic legacy time switch enclosures.
- ▶ Remote access - once connected to a WiFi network, the PE700 series can be accessed via the Intermatic Connect app from any location.
- ▶ Override inputs - remotely extend or override active schedules at any time with a switch, photocontrol, presence sensor or via the Intermatic Connect app.
- ▶ Auto voltage - automatic input voltage selection from 120 VAC to 277 VAC, 50/60 Hz.
- ▶ Configurable relay outputs for multiple switching options (SPDT or DPDT).
- ▶ Service mode - with optional timed-stop or timed-run feature. Locks external users out from controlling connected loads remotely.
- ▶ LED Status Indicators - provides visual cue to indicate the devices current state and connection status.
- ▶ Non-volatile EEPROM memory protects programing indefinitely.

APPLICATIONS

- ▶ Motor Control
- ▶ Pump Control
- ▶ Pool Lighting Control

TECHNICAL DATA

General

Model Number	PE723P
Description	24-Hour 7-Day Electronic WiFi Time Control, 2-Circuit, Type 3R Plastic Enclosure
UPC Code	078275154032
Brand	Intermatic
Country of Origin (Intermatic)	THAILAND
Warranty Period	3-Year limited

Control Specifications

Maximum ON/OFF Operations	96
Operation Mode	24 hour; 7 day
Backup Type	Battery
Battery Type	CR2032

Mechanical Specifications

Enclosure Type	Outdoor type 3R plastic
----------------	-------------------------

Dimensions

Product Dimensions (H x W x D) in	7.5 x 8.87 x 3 in
-----------------------------------	-------------------

Load Ratings

Electronic Ballast Load Ratings NO Ranges	16 A per circuit (NO)
Motor Load Ratings Ranges	1 HP @ 120 VAC, 2 HP @ 240 VAC, FLA 16 A and LRA of 96 A @ 120 VAC (NO), FLA 15 A and LRA of 90 A @ 240 VAC (NO)

Electrical Specifications

Voltage Selection Type	Auto Voltage
Input Voltage Range(s)	120-277 VAC, 50/60 Hz
Number of Circuits	3
Switch Type	3xSPST

Packaging

Shipping Weight (lbs)	2.39
Unit Carton Dimensions (H x W x L) in	4.375 x 9.5 x 10 in

Environmental Specifications

Temperature (operation)	-40 °F to 158 °F / (-40 °C to 70 °C)
-------------------------	--------------------------------------

Standards and Certifications

UL Certification	cULus
California Proposition 65	DEHP; Lead
RoHS Certification	Yes