

## Item Bundle - Freeze Protection 4/8 Breaker Base Panel with 2 Timers and Thermostat for 240V Cleaner Applications, Heater Protection, Type 3R Metal Enclosure

Item PF1222TB1



### PRODUCT DESCRIPTION

Protects pool/spa equipment against freeze damage.

### FEATURES

- ▶ GFCI and switch mounting capabilities
- ▶ Turns pump and heater ON when outdoor temperature drops below user-adjustable setpoint on thermostat
- ▶ Heavy-duty Type 3R metal indoor/outdoor enclosure

### APPLICATIONS

- ▶ Protection
- ▶ Pump Control

### TECHNICAL DATA

#### General

Model Number	PF1222TB1
Description	Freeze Protection 4/8 Breaker Base Panel with 2 Timers and Thermostat for 240V Cleaner Applications, Heater Protection, Type 3R Metal Enclosure
UPC Code	078275141131
Brand	Intermatic
Country of Origin (Intermatic)	MEXICO
Warranty Period	1-Year limited

#### Control Specifications

Heater Protection Switch	Yes
--------------------------	-----

#### Mechanical Specifications

Number of Breaker Knockouts	4
Enclosure Type	3R Beige metal

#### Dimensions

Product Dimensions (H x W x D) in	16.875 x 10.875 x 4.75 in
-----------------------------------	---------------------------

#### Material Specifications

Color	Beige
-------	-------

#### Load Ratings

Load Center Ratings	100 A, 120-208 VAC, 60 Hz;85 A, 120-208 VAC, 60 Hz;80 A;80 A, 208 VAC, Single Phase;60 A;60 A, 208 VAC, Single Phase;125 A;125 A, 208 VAC, Single Phase;80 A, 240 VAC, 60 Hz, Single Phase;80 A, 120-240 VAC, 50 Hz;80 A, 120 VAC, 60 Hz;60 A, 240 VAC, 60 Hz, Single Phase;60 A, 120-240 VAC, 50 Hz;60 A, 120-208 VAC, 60 Hz;125 A, 240 VAC, 60 Hz, Single Phase;125 A, 120-240 VAC, 50 Hz;125 A, 120-208 VAC, 60 Hz;100 A, 240 VAC, 60 Hz, Single Phase;85 A, 240 VAC, 60 Hz, Single Phase
Load Center Rating Display	60 A Max, 120/240 VAC, Single Phase, 60 Hz
Motor Load Ratings Ranges	3 HP @ 240 VAC, 60 Hz

**Electrical Specifications**

Number of Circuits	2
Switch Type	DPST
Maximum Power Consumption (W)	3 W
Number of Receptacle/Switch Knockouts	1

**Packaging**

Shipping Weight (lbs)	18.712
Unit Carton Dimensions (H x W x L) in	6.25 x 12.25 x 18.25 in

**Operating Specifications**

Thermostat Range Minimum (°C)	0.5
Thermostat Range Minimum (°F)	33
Thermostat Range Maximum (°C)	6
Thermostat Range Maximum (°F)	42

**Standards and Certifications**

CSA Certification	cCSAus
California Proposition 65	Lead

---

## ACCESSORIES



156T1978A  
Extra/replacement trippers 1 ON and 1 OFF



21T166A  
Spacer-Standoff, 3" long - 2 pack



21T156A  
Spacer-Standoff, 3" long - 4 pack