

## Item Bundle - Control Panel with T104M Mechanism

Item T10004R



### PRODUCT DESCRIPTION

Can be used as a power center only, or add mechanisms or wiring devices for complete control systems.

### FEATURES

- ▶ Available with one or two heavy-duty time switch mechanisms
- ▶ Accepts any combination of PF1000M, P1403ME, P1353ME, P4043ME, P4243ME, T100M or RC2000M Series mechanisms
- ▶ Load center dead front has two knockouts for switches or GFCIs and one on the side
- ▶ Wiring devices may be installed in these load centers with the use of Standoffs, sold separately below
- ▶ Control two-speed pumps with the T10604R

### APPLICATIONS

- ▶ Distribution/Control Panel
- ▶ Motor Control
- ▶ Pump Control

### TECHNICAL DATA

#### General

|                                |                                    |
|--------------------------------|------------------------------------|
| Model Number                   | T10004R                            |
| Description                    | Control Panel with T104M Mechanism |
| UPC Code                       | 078275116801                       |
| Brand                          | Intermatic                         |
| Country of Origin (Intermatic) | MEXICO                             |
| Warranty Period                | 1-Year limited                     |

#### Mechanical Specifications

|                |                |
|----------------|----------------|
| Enclosure Type | 3R Beige metal |
|----------------|----------------|

#### Dimensions

|                                   |   |
|-----------------------------------|---|
| Product Dimensions (H x W x D) in | 12.875 x 10.875 x 4.75 in                                 |
| Knockout Dimensions Bottom        | (5) combination 1/2" - 3/4" and (2) combination 3/4" - 1" |
| Knockout Dimensions Back          | (1) combination 1/2" - 3/4" and (1) 3/4" - 1"             |
| Knockout Dimensions Left          | (1) combination 1/2" - 3/4"                               |
| Knockout Dimensions Right         | (1) 1 3/4" x 2 3/4"                                       |

#### Material Specifications

|       |       |
|-------|-------|
| Color | Beige |
|-------|-------|

#### Load Ratings

|                                |  |
|--------------------------------|--|
| Tungsten Range(s)              | 40 A, 120-240 VAC, 60 Hz   |
| Inductive                      | 40 A, 240 VAC, 60 Hz; 40 A, 208 VAC, 60 Hz; 40 A, 120 VAC, 60 Hz |
| Resistive Load Ratings Ranges  | 40 A, 120-240 VAC, 60 Hz   |
| Inductive Load Ratings Ranges  | 40 A, 120-240 VAC, 60 Hz   |
| Pilot Duty Load Ratings Ranges | 1000 VA, 120-240 VAC, 60 Hz                                      |
| Mechanism Supply Voltage       | 240 VAC, 60 Hz   |

|                           |  |
|---------------------------|--|
| Mechanisms                | (1) T104M  |
| Motor Load Ratings Ranges | 2 HP, 24 FLA @ 120 VAC, 60 Hz; 5 HP, 28 FLA @ 240 VAC, 60 Hz |

#### Electrical Specifications

|                                       |      |
|---------------------------------------|------|
| Number of Circuits                    | 1    |
| Switch Type                           | DPST |
| Maximum Power Consumption (W)         | 3 W  |
| Number of Receptacle/Switch Knockouts | 2    |

#### Packaging

|                                       |                         |
|---------------------------------------|-------------------------|
| Shipping Weight (lbs)                 | 10.478                  |
| Unit Carton Dimensions (H x W x L) in | 5.63 x 12.06 x 13.81 in |

#### Environmental Specifications

|                         |                                      |
|-------------------------|--------------------------------------|
| Temperature (operation) | -40 °F to 130 °F / (-40 °C to 54 °C) |
|-------------------------|--------------------------------------|

#### Standards and Certifications

|                           |        |
|---------------------------|--------|
| CSA Certification         | cCSAus |
| California Proposition 65 | Lead   |

---

## ACCESSORIES



156T1978A  
Extra/replacement trippers 1 ON and 1 OFF



21T166A  
Spacer-Standoff, 3" long - 2 pack



21T156A  
Spacer-Standoff, 3" long - 4 pack



22T338GR  
Mounting Bracket for Intermatic Standardized  
Timer Mechanisms