

Mechanical Time Switch - 24-Hour 120V Mechanical Time Switch, SPST, Pool Heater Protection, Type 3R Plastic Enclosure

Item T101P201



PRODUCT DESCRIPTION

Heavy-duty mechanical time switches control a single load

FEATURES

- ▶ Highest motor load ratings in the industry
- ▶ 12 ON/OFF operations per day
- ▶ One ON and one OFF tripper included
- ▶ Available with pool heater protection
- ▶ Teeter-type terminals for multiple load connections

APPLICATIONS

- ▶ Heater Thermostat Control
- ▶ Motor Control
- ▶ Pump Control

TECHNICAL DATA

General	
Model Number	T101P201
Description	24-Hour 120V Mechanical Time Switch, SPST, Pool Heater Protection, Type 3R Plastic Enclosure
UPC Code	078275700574
Brand	Intermatic
Country of Origin (Intermatic)	MEXICO
Warranty Period	1-Year limited
Control Specifications	
Maximum ON/OFF Operations	12
Operation Mode	24 hour
Application Compatibilities	LED
Mechanical Specifications	
Enclosure Type	Outdoor type 3R plastic
Dimensions	
Product Dimensions (H x W x D) in	10 x 6.5 x 4 in
Knockout Dimensions Bottom	(2) 1/2" and 3/4"
Knockout Dimensions Back	1/2" and 3/4" combination
Load Ratings	
Tungsten Range(s)	40 A, 120-480 VAC, 60 Hz
Electronic Ballast	16 A
Electronic Ballast Load Ratings Ranges	16 A, 120 VAC
Inductive	40 A @ Varying Voltages, 60 Hz; 40 A, 277 VAC, 60 Hz; 40 A, 240 VAC, 60 Hz; 40 A, 208 VAC, 60 Hz; 40 A, 120 VAC, 60 Hz

Motor	2 HP, 24 FLA @ 120 VAC, 60 Hz; 5 HP, 28 FLA @ 240 VAC, 60 Hz
-------	--

Resistive Load Ratings Ranges	40 A, 120-480 VAC, 60 Hz
-------------------------------	--------------------------

Inductive Load Ratings Ranges	40 A, 120-480 VAC, 60 Hz
-------------------------------	--------------------------

Pilot Duty Load Ratings Ranges	1000 VA, 120-480 VAC, 60 Hz
--------------------------------	-----------------------------

Electrical Specifications

Heater Control Output	10 A, 250 VAC MAX, 60 Hz
-----------------------	--------------------------

Wiring Option	Terminals
---------------	-----------

Input Voltage Range(s)	120 VAC, 60 Hz
------------------------	----------------

Number of Circuits	1
--------------------	---

Switch Type	SPST
-------------	------

Maximum Power Consumption (W)	3 W
-------------------------------	-----

Packaging

Unit Carton Dimensions (H x W x L) in	4.25 x 7.31 x 11.75 in
---------------------------------------	------------------------

Environmental Specifications

Temperature (operation)	-40 °F to 130 °F / (-40 °C to 54 °C)
-------------------------	--------------------------------------

Standards and Certifications

UL Certification	cULus
------------------	-------

CSA Certification	cCSAus
-------------------	--------

Other Certifications and Compatibilities	LED
--	-----

California Proposition 65	Lead
---------------------------	------

ACCESSORIES



156T1978AMX
1 Set of ON/OFF Trippers for T100, T7000,
and WH40



156T1978A
Extra/replacement trippers 1 ON and 1 OFF



124T2411A
Insulator for Mechanical Time Switches - 10
Pack

Product
Image
Not
Available

156T1957A
Skipper Screws (3 per package)



22T338GR
Mounting Bracket for Intermatic Standardized
Timer Mechanisms

Product
Image
Not
Available

WG430-20D
MOTOR-BOXED, 125V 60HZ