


## Electromechanical Time Switch - Mechanical Water Heater Time Switch

Item T104-20



### PRODUCT DESCRIPTION

With the easy-to-set "Yellow Dial," these time switches allow for basic control of electric water heaters. These time switches offer a minimum ON/OFF time of one hour, and are available for 208-250 VAC applications. With the proven reliability of our mechanical line, these time switches provide dependable electric water heater control.

### FEATURES

- ▶ Two sets of ON/OFF trippers
- ▶ Enables shifting electricity use into off-peak hours to reduce energy costs
- ▶ Convenient external override switch
- ▶ Up to 12 ON/12 OFF events

### APPLICATIONS

- ▶ Agriculture Feeders
- ▶ Greenhouse Misting Control
- ▶ Water Heater Control

### TECHNICAL DATA

#### General

Model Number	T104-20
Description	Mechanical Water Heater Time Switch
UPC Code	078275000131
Brand	Intermatic
Country of Origin (Intermatic)	MEXICO
Warranty Period	1-Year limited

#### Control Specifications

Minimum ON/OFF Times	1 hour
Maximum ON/OFF Operations	12
Operation Mode	24 hour
Mechanism Type	Analog/Mechanical
Has Manual Override	Yes
Has Override Switch	Yes
Application Compatibilities	Electric Water Heater

#### Mechanical Specifications

Enclosure Type	Indoor type 1 metal
Number of Trippers Included	2 ON/2 OFF

#### Dimensions

Product Dimensions (H x W x D) in	7 7/8 x 5 1/8 x 3 7/16 in
Wire Size Min	#14 AWG
Wire Size Max	#8 AWG
Knockout Dimensions Bottom	(2) combination 1/2" - 3/4"
Knockout Dimensions Back	(1) combination 1/2" - 3/4"
Knockout Dimensions Left	(1) combination 1/2" - 3/4"

**Load Ratings**

Resistive Load Ratings Ranges	40 A Max, 208-277 VAC, 60 Hz
Clock Motor Voltage	208/277 VAC, 60 Hz

**Electrical Specifications**

Wiring Option	Terminals
Input Voltage Range(s)	208-277 VAC, 60 Hz
Switch Type	DPST
Maximum Power Consumption (W)	3 W
Amps Per Pole	40 A
Watts Resistive	10000

**Packaging**

Unit Carton Dimensions (H x W x L) in	8.5 x 3.5 x 5.5 in
---------------------------------------	--------------------

**Environmental Specifications**


Temperature (operation)	-40 °F to 130 °F / (-40 °C to 54 °C)
-------------------------	--------------------------------------

**Standards and Certifications**

UL Certification	cULus
CSA Certification	cCSAus
UL File Number	UL917
California Proposition 65	Lead

---

## ACCESSORIES



22T338GR

Mounting Bracket for Intermatic Standardized Timer Mechanisms