

Mechanical Time Switch - 24-Hour 208-277V Mechanical Time Switch, SPDT, Type 3R Plastic Enclosure

Item T106P3



PRODUCT DESCRIPTION

Heavy-duty mechanical time switches control a single load

FEATURES

- Highest motor load ratings in the industry
- ► 12 ON/OFF operations per day
- ► One ON and one OFF tripper included
- Available with pool heater protection
- ► Teeter-type terminals for multiple load connections

APPLICATIONS

- ► Heater Thermostat Control
- Motor Control
- Pump Control
- Water Circulation

TECHNICAL DATA

General	
Model Number	T106P3
Description	24-Hour 208-277V Mechanical Time Switch, SPDT, Type 3R Plastic Enclosure
UPC Code	078275135222
Brand	Intermatic
Country of Origin (Intermatic)	MEXICO
Warranty Period	1-Year limited
Control Specifications	
Maximum ON/OFF Operations	12
Operation Mode	24 hour
Application Compatibilities	LED
Mechanical Specifications	
Enclosure Type	Outdoor type 3R plastic
Enclosure Type	Outdoor type 3R plastic
Enclosure Type Dimensions	Outdoor type 3R plastic
	Outdoor type 3R plastic 10 x 6.5 x 4 in
Dimensions	
Dimensions Product Dimensions (H x W x D) in	10 x 6.5 x 4 in
Dimensions Product Dimensions (H x W x D) in Knockout Dimensions Bottom	10 x 6.5 x 4 in (2) 1/2" and 3/4"
Dimensions Product Dimensions (H x W x D) in Knockout Dimensions Bottom	10 x 6.5 x 4 in (2) 1/2" and 3/4"
Dimensions Product Dimensions (H x W x D) in Knockout Dimensions Bottom Knockout Dimensions Back	10 x 6.5 x 4 in (2) 1/2" and 3/4"
Dimensions Product Dimensions (H x W x D) in Knockout Dimensions Bottom Knockout Dimensions Back Load Ratings	10 x 6.5 x 4 in (2) 1/2" and 3/4" 1/2" and 3/4" combination
Dimensions Product Dimensions (H x W x D) in Knockout Dimensions Bottom Knockout Dimensions Back Load Ratings Tungsten Range(s)	10 x 6.5 x 4 in (2) 1/2" and 3/4" 1/2" and 3/4" combination 40 A, 120-240 VAC, 60 Hz
Dimensions Product Dimensions (H x W x D) in Knockout Dimensions Bottom Knockout Dimensions Back Load Ratings Tungsten Range(s) Electronic Ballast	10 x 6.5 x 4 in (2) 1/2" and 3/4" 1/2" and 3/4" combination 40 A, 120-240 VAC, 60 Hz 16 A



Resistive Load Ratings Ranges	40 A, 120-240 VAC, 60 Hz
Inductive Load Ratings Ranges	40 A, 120-240 VAC, 60 Hz
Pilot Duty Load Ratings Ranges	1000 VA, 120-240 VAC, 60 Hz
Electrical Specifications	
Heater Control Output	10 A, 250 VAC MAX, 60 Hz
Wiring Option	Terminals
Input Voltage Range(s)	208-277 VAC, 60 Hz
Number of Circuits	1
Switch Type	1 NO/1 NC
Maximum Power Consumption (W)	3 W
Packaging	
Unit Carton Dimensions (H x W x L) in	10.06 x 4 x 6.56 in
Environmental Specifications	
Temperature (operation)	-40 °F to 130 °F / (-40 °C to 54 °C)
Standards and Certifications	
UL Certification	cULus
CSA Certification	cCSAus
Other Certifications and Compatibilities	LED
California Proposition 65	Lead



ACCESSORIES






156T1978A



124T2411A Insulator for Mechanical Time Switches - 10 Skipper Screws (3 per package) Pack



156T1957A



156T1978AMX



22T338GR Mounting Bracket for Intermatic Standardized Timer Mechanisms