

# Weather Proof Cover - Extra-Duty Plastic In-Use Weatherproof Cover, Single-Gang, Vrt/Hrz, 2.25" Black

Item WP5000BL



**PRODUCT DESCRIPTION** 

Plastic In-Use Weatherproof Covers are extra-duty rated and easy to install. Covers come with a gasket, mounting screws, base, cover assembly and inserts to meet the needs of a variety of applications.

#### **FEATURES**

- ► Complies with 2020 NEC Article 406.9 (B)(1) for wet locations and extra-duty applications
- ► CEC Article 26-702 Compliant
- ► UL Certified for Type 3R outdoor enclosures
- Meets requirements for cold impact testing: -60° F (-51° C)
- > Heavy-duty UV stabilized polycarbonate cover, mounting base and inserts
- ► 1/8" (3 mm) thick, neoprene gasket with slits for mounting screws
- ► Lockable hasp: All models accept up to 1/4" (6 mm) dia shank
- Impact rated: 12 lbf. impact test to ensure cover remains intact
- Reinforced hinge pin designed to exceed 40 lbf. hinge hang/stress test
- Warranty: 1-year limited


## **APPLICATIONS**

► Receptacle Protection

## **TECHNICAL DATA**

շանու

General	
Model Number	WP5000BL
Description	Extra-Duty Plastic In-Use Weatherproof Cover, Single-Gang, Vrt/Hrz, 2.25" Black
UPC Code	078275145580
Brand	Intermatic
Country of Origin (Intermatic)	MEXICO
Warranty Period	1-Year limited
Mechanical Specifications	
Number of Included Inserts	3
Insert Types Included	WP17
Hinge Direction	Vertical/Horizontal
Is Extra-Duty Rated	Yes
Dimensions	
Product Dimensions (H x W x D) in	6.33333333333333 x 4.6666666666666666 x 2.25 in
Accepted Cord Size Max	2x14 AWG; 1x12 AWG
Вох Туре	Single
Material Specifications	
Color	Black
Weatherproof Cover Material	UV Stabilized Plastic
Packaging	
Shipping Weight (lbs)	0.5






Unit Carton Dimensions (H x W x L) in	6.5 x 2.75 x 4.75 in
Standards and Certifications	
UL Certification	cULus
California Proposition 65	None
RoHS Certification	N/A



#### DRAWINGS AND DIAGRAMS





## ACCESSORIES



WP17 Single-Gang Inserts (3)