# ICPL526RE Series 5" 26W Triple Vertical CFL Remodel Housing IC Rated



## Features

- 5" Remodel housing
- Energy Star® qualified, California Title 24 compliant
- 120V HPF or NPF rapid start electronic FCC Class B ballast with end-of-life lamp protection
- Ballast mounted to underside of J-box to minimize contact with insulation
- Removable or fixed mounted socket accommodates a variety of trim installations
- Remodel springs accommodate up to 1 1/8" ceiling thickness
- Fully assembled housing
- Pre-wired junction box with (5) 1/2" knockouts with pryout slots, (4) non-metallic sheathed cable connectors, and ground wire
- UL Listed, C-UL/CSA certified
- Shadow-free, knife-edge trim design blends smoothly into the ceiling and allows architectural continuity with Aculux® trims
- 2 year warranty
- One 26W triple tube (4-pin) CFL lamp with trim selection on page 58



## Description

IC rated Air-Loc, energy efficient vertical CFL remodel housing for remodel applications where back side of ceiling is not accessible • Can be completely covered with insulation • Air-Loc installation stops infiltration and exfiltration of air, reducing heating and cooling costs

## Listings

Accessories Catalog Number

ALG5R

SMPLT-5

UL Listed, C-UL Listed/CSA certified for damp and wet locations • Washington State, IECC and MEC energy codes as tested per ASTM-E283 • Energy Star® qualified, California Title 24 compliant • Wet location listed when used with 210, 2130 and 5101 trims

Description

housings

and 24" joists.

Air-Loc® Energy Conserving Gasket


Galvanized steel plate for locating remodel style housings. Screw/nail holes for full coverage between 16"


Kit for 5" Air-Loc IC Remodel

## **Ordering Information**

	ICPL526RE - 120V HPF ballast
Catalog Number:	ICPL526REN - 120V NPF ballast
Catalog Number:	ICPL526REN-DB120 - ICPL526RE
-	with 120V normal power factor
	(NPF) dimmable ballast — T24
	and Energy Star <sup>®</sup> compliant

### Dimensions





5 1/2" Ceiling Cutout

