

## Features

- 6" Standard slope remodel housing (oval)
- Oblique angle housing design holds trims flush with the ceiling
- Adjustable socket plate permits lamp to remain perpendicular to floor through entire pitch range
- Medium base porcelain socket with nickel-plated copper screw shell
- Housing is vertically adjustable to accommodate up to a 1" ceiling thickness
- Housing is secured in place with factory supplied remodel clips
- Telescoping height for use in 2x8 or 2x10 construction
- Pre-wired junction box with (4) 1/2" knockouts with pryout slots, (4) non-metallic sheathed cable connectors, and ground wire
- Shadow-free, knife-edge trim design blends smoothly into the ceiling and allows architectural continuity with Aculux® trims
- Angle-cut baffles ensure grooves remain parallel to the floor to provide proper optics
- UL Listed, C-UL/CSA certified for through-branch wiring, maximum (4) #12 AWG branch circuit conductors (2 in, 2 out)
- Thermally protected against improper use of lamps
- Lamp wattage ratings and apertures based on trim selection on page 116



## Description

Non-IC rated remodel housing for use in 2/12 to 6/12 pitch slopes (9° to 27°) where the back side of the ceiling is not accessible • Designed to be installed in non-insulated areas, or where insulation is spaced at least 3" from housing • The Juno patented Slope Ceiling Down-Lites direct light straight down, providing proper lighting from a sloped surface

## Listings

UL Listed, C-UL/CSA certified for through-branch wiring, damp and wet locations • Wet location listed with the 610 trim • Conforms with City of Chicago IP requirements

## Ordering Information

Catalog Number: **TC926R**

## Dimensions

