


### Trac 12/25 Low Voltage Trac System

The Trac 12/25 system combines the 25-amp capacity of 10 gauge conductors with a miniature rigid profile that can be surface mounted or pendant suspended. The system operates off of remotely located 12-volt or 24-volt transformers. A maximum of 300 watts (12 volts) or 600 watts (24 volts) can be placed per circuit of trac.

#### Key Features

- 10 gauge solid copper conductors with 25-amp capacity
- Rigid aluminum miniature 5/8" H x 15/16" W profile
- Accepts all standard Trac 12™ lampholders
- Can be surface or pendant mounted
- Can be cut to length by installer



Catalog #	Finish	Description	Dimensions
TLR2WH	White	2' trac (actual length 20 5/8")	
TLR2BL	Black		
TLR2SL	Silver		
TLR4WH	White	4' trac (actual length 44 5/8")	
TLR4BL	Black		
TLR4SL	Silver		
TLR6WH	White	6' trac (actual length 68 5/8")	
TLR6BL	Black		
TLR6SL	Silver		
TLR8WH	White	8' trac (actual length 92 5/8")	
TLR8BL	Black		
TLR8SL	Silver		

Trac 12/25 Trac Sections include dead-end and mounting hardware

### Electrical Feeds and Dead End

	Catalog #	Finish	Description	Dimensions
<p>End Feed Connector and Outlet Box Cover</p>	TLR21WH	White	<ul style="list-style-type: none"> <li>• Allows trac to be fed via remote transformer from an outlet box</li> <li>• Includes terminal block, cover and mounting plate</li> </ul>	
	TLR21BL	Black		
	TLR21SL	Silver		
<p>End Feed Connector</p>	TLR38WH	White	<ul style="list-style-type: none"> <li>• Allows trac to be fed via remote transformer from above using standard 1/2" electrical connector</li> <li>• Includes terminal block feed connector and cover</li> </ul>	
	TLR38BL	Black		
	TLR38SL	Silver		
<p>End Feed Connector and Conduit Feed</p>	TLR34WH	White	<ul style="list-style-type: none"> <li>• Allows trac to be fed via remote transformer with conduit through the end or top using standard 1/2" electrical connector</li> <li>• Includes terminal block feed connector, mounting plate and cover</li> </ul>	
	TLR34BL	Black		
	TLR34SL	Silver		
<p>Pendant End Feed Connector</p>	TLR50WH	White	<ul style="list-style-type: none"> <li>• Use with TLR90, TLR91 or TLR96 to feed from end of trac</li> <li>• Includes terminal block feed connector, mounting plate and cover</li> </ul>	
	TLR50BL	Black		
	TLR50SL	Silver		
<p>Outlet Box/T-Bar Ceiling Feed Canopy</p>	TLR36WH	White	<ul style="list-style-type: none"> <li>• Mounts over outlet boxes or on T-Bar ceiling to feed up to four tracs</li> <li>• Includes one terminal block connector, mounting plate and cover</li> <li>• To feed more than one trac, order additional TLR36TB connectors</li> <li>• Requires T-Bar clip (TLR37) for T-Bar installation</li> </ul>	
	TLR36BL	Black		
	TLR36SL	Silver		
	TLR36TB-WH	White		
TLR36TB-BL	Black			
<p>Dead End</p>	TLR28WH	White	<ul style="list-style-type: none"> <li>• Dead end to use on extra field-cut trac sections</li> </ul>	
	TLR28BL	Black		
	TLR28SL	Silver		