



## 5822-W

20 Amp Duplex Receptacle/Outlet, Commercial Grade, Self-Grounding

Duplex Receptacle Outlet, Commercial Specification Grade, Indented Face, 20 Amp, 250 Volt, Side Wire, NEMA 6-20R, 2-Pole, 3-Wire, Self-Grounding - White

**ROHS Compliant** : Yes

### Technical Information

AC Horsepower Ratings

**At Rated Voltage** : 2 HP

Electrical Specifications

**Amperage** : 20 A

**Current Limiting** : Full Rated Current

**Dielectric Voltage** :  
Withstands 2000V per UL498

**Grounding** : Self-Grounding

**Pole** : 2

**Temperature Rise** : Max 30C  
after 100 cycles OL at 150  
percent rated current

**Voltage** : 250 VAC

**Wire** : 3

Environmental Specifications

**Flammability** : Rated V-2 per  
UL 94

**Operating Temperature** : -40°  
C to 60°C

Material Specifications

**Body Material** : Nylon

**Color** : White

**Face Material** : Nylon

**Ground Clips** : Brass-Plated

**Grounding Screw** : Brass 8-32

**Line Contacts** : Brass Double  
Wipe .031 Thick

**Strap Material** : Zinc-Plated  
Steel

**Terminal Screws** : Brass 8-32

Mechanical Specifications

**Product ID** : Ratings are  
permanently marked on device

**Screw Terminal Torque** : 14-  
18 in-lbs

**Terminal Accom.** : 14-10 AWG

**Terminal ID** : Brass-Hot,  
Green-Ground, Silver-Neutral

Product Features

**Body Material** : Nylon

**Color** : White

**Device Type** : Duplex  
Receptacle Outlet


**Feature 4** : Indented Face

**Grade** : Commercial  
Specification Grade

**Color** :  White

**UPC Code** : 078477790434

**Country Of Origin** : United States

**NEMA** :  6-20R

**Available Colors** :

  
Brown

  
Ivory

**Termination** : Side Wire

**Grounding** : Self-Grounding

**NEMA** : 6-20R

Standards and Certifications

**ANSI** : C-73

**CSA C22.2 No. 42** : File  
152105


**NEMA** : WD-2 WD-6

**NOM** : 057

**UL498** : File E13399

**Warranty** : 10-Year Limited

## Wiring Diagram



### SPECIFICATION SUBMITTAL

<p><b>JOB NAME:</b></p> <input type="text"/>	<p><b>CATALOG NUMBERS:</b></p> <input type="text"/>
<p><b>JOB NUMBER:</b></p> <input type="text"/>	<input type="text"/>

#### Leviton Manufacturing Co., Inc

201 North Service Road, Melville, NY 11747

Telephone: +1-800-323-8920 · FAX: +1-800-832-9538 · Tech Line (8:30AM-7:30PM E.S.

T. Monday-Friday): +1-800-824-3005

#### Leviton Manufacturing of Canada, Ltd.

165 Hymus Boulevard, Pointe Claire, Quebec H9R 1E9 · Telephone: +1-800-469-7890 ·

FAX: +1-800-824-3005 · [www.leviton.com/canada](http://www.leviton.com/canada)

#### Leviton S. de R.L. de C.V.

Lago Tana 43, Mexico DF, Mexico CP 11290 · Tel.: (+52)55-5082-1040 · FAX: (+52)

5386- 1797 · [www.leviton.com.mx](http://www.leviton.com.mx)

**Visit our Website at:** [www.leviton.com](http://www.leviton.com)

© 2024 Leviton Manufacturing Co., Inc. All Rights Reserved. Subject to change without notice.

#### Leviton has a global presence.

If you would like to know where your local Leviton office is located please go to:

[www.leviton.com/international/contacts](http://www.leviton.com/international/contacts)

© 2024 Leviton Manufacturing Co., Inc.