



8827-CW4

660W/250V Medium Base One-Piece White Urea Outlet Box Mount Incandescent Lampholder, Pull Chain, Single Circuit, 2 Screws with Captive Clamps, Top Wired - White

ROHS Compliant : Yes

Leviton produces lamp holders for virtually every light source equipped with incandescent, fluorescent, or LED lamps. Lamp-holders include incandescent medium base, and specialty sizes & fluorescent lamp holders, in addition to a large line of porcelain lamp holders including pulse-rated mogul-base products, and an extensive selection of devices for high-intensity lamps.

UPC Code : 078477103128

Country Of Origin : Please Contact Customer Service

Technical Information

Electrical Specifications

Availability : Distribution

Circuit : Single Circuit

Construction : One-Piece

Fits Outlet Box Size : 3-1/4 or 4 Inch

Lamp Socket Base : Medium

Max. Lamp Wattage : 660W

Mounting Type : Twist-Lock

Operator Type : Pull Chain

Sequence : ON-OFF

Standards and Certifications : UL/CSA

Termination : 2 Terminal Screws w/Captive Clamps

Voltage : 250 VAC

Warranty : 1-Year Limited

Wiring Access : Top Wired

Mechanical Specifications

Availability : Distribution

Body Material : White Urea

Circuit : Single Circuit

Color : White

Construction : One-Piece

Fits Outlet Box Size : 3-1/4 or 4 Inch

Lamp Socket Base : Medium

Mounting Type : Twist-Lock

Material Specifications

Availability : Distribution

Body Material : White Urea

Circuit : Single Circuit

Color : White

Fits Outlet Box Size : 3-1/4 or 4 Inch

Lamp Socket Base : Medium

Mounting Type : Twist-Lock

Operator Type : Pull Chain

Sequence : ON-OFF

Shell Material : Aluminum

Socket Shell Material : Aluminum

Termination : 2 Terminal Screws w/Captive Clamps

Product Features

Construction : One-Piece

Lamp Base : Medium

Lampholder Type : Outlet Box Mount

Light Type : Incandescent

Max. Lamp Wattage : 660W

Sequence : ON-OFF

Standards and Certifications : UL/CSA

Voltage : 250 VAC

Operator Type : Pull Chain

Warranty : 1-Year Limited

Socket Shell Material :
Aluminum

Wiring Access : Top Wired

Termination : 2 Terminal
Screws w/Captive Clamps

Torque Range : 14 – 18 in.-lbs

Standards and Certifications

CSA Certified : File LR-1863

UL Listed : File E3810

SPECIFICATION SUBMITTAL

JOB NAME: <input type="text"/>	CATALOG NUMBERS: <input type="text"/>	<input type="text"/>
JOB NUMBER: <input type="text"/>	<input type="text"/>	<input type="text"/>

Leviton Manufacturing Co., Inc

201 North Service Road, Melville, NY 11747

Telephone: +1-800-323-8920 · FAX: +1-800-832-9538 · Tech Line (8:30AM-7:30PM E.S.

T. Monday-Friday): +1-800-824-3005

Leviton Manufacturing of Canada, Ltd.

165 Hymus Boulevard, Pointe Claire, Quebec H9R 1E9 · Telephone: +1-800-469-7890 ·

FAX: +1-800-824-3005 · www.leviton.com/canada

Leviton S. de R.L. de C.V.

Lago Tana 43, Mexico DF, Mexico CP 11290 · Tel.: (+52)55-5082-1040 · FAX: (+52)

5386- 1797 · www.leviton.com.mx

Visit our Website at: www.leviton.com

© 2024 Leviton Manufacturing Co., Inc. All Rights Reserved. Subject to change without notice.

Leviton has a global presence.

If you would like to know where your local Leviton office is located please go to:

www.leviton.com/international/contacts

© 2024 Leviton Manufacturing Co., Inc.