



Shown actual size: Fassada® 1-gang wallplate in matte ivory (IV)

available colors

colors (matte finish) (see page 14 for color swatches)

- | | |
|------------------|------------------------|
| WH white | LA light almond |
| IV ivory | BL black |
| AL almond | |

colors (gloss finish) (see page 12 for color swatches)

- | | |
|------------------|------------------------|
| WH white | LA light almond |
| IV ivory | BL black |
| AL almond | |

colors (metal finish)

- | |
|---------------------------|
| SS stainless steel |
|---------------------------|

Fassada® wallplates

product family features





- wallplates feature clean appearance with no visible hardware
- coordinate with Lutron® dimmers, switches, and systems
- multiple devices with line and low-voltage can be mounted behind a common wallplate using a standard barrier backbox (see Application Note #213) at www.lutron.com/applicationnotes

Questions on installation or selection?
Call Lutron® 24 hours/7 days a week at
1.800.523.9466 or visit www.lutron.com

wallplates






traditional opening – matte

1-gang	FW-1-	
W: 2.86" (73mm); H: 4.60" (117mm); D: .23" (5.8mm)		
2-gang	FW-2-	
W: 4.67" (119mm); H: 4.60" (117mm); D: .23" (5.8mm)		
3-gang	FW-3-	
W: 6.48" (165mm); H: 4.60" (117mm); D: .23" (5.8mm)		
4-gang*	FW-4-	
W: 8.29" (211mm); H: 4.60" (117mm); D: .23" (5.8mm)		

* not available in stainless steel


traditional opening – gloss

1-gang	FG-1-	
W: 2.86" (73mm); H: 4.60" (117mm); D: .23" (5.8mm)		
2-gang	FG-2-	
W: 4.67" (119mm); H: 4.60" (117mm); D: .23" (5.8mm)		
3-gang	FG-3-	
W: 6.48" (165mm); H: 4.60" (117mm); D: .23" (5.8mm)		



rotate the wallplate for small/large or large/small opening applications

combination opening (gloss & stainless steel only)

2-gang (1 large, 1 small opening)	FW-2-TD-SS	
W: 4.67" (119mm); H: 4.60" (117mm); D: .23" (5.8mm)		
2-gang (1 large, 1 small opening)	FG-2-TD-	
W: 4.67" (119mm); H: 4.60" (117mm); D: .23" (5.8mm)		

Multiple devices with line and low-voltage can be mounted behind a common wallplate using a standard barrier backbox (see Application Note #213) at www.lutron.com/applicationnotes

See above for available colors.
To order, add color suffix to model number.
Example: **FW-1- WH**

All Lutron® wallplates are screwless, seamless, and have no visible hardware. There are two parts:
1) alignment adapter plate
2) front plate – securely snaps onto alignment adapter plate

Controls must have heat-sink fins broken for multi-gang installations. Removing this metal reduces the amount of heat that the control can dissipate, thus reducing the wattage capacity of the control.

Please derate dimmers and switches (page 182) as required.

available colors

colors (matte finish) (see page 14 for color swatches)

WH white	LA light almond
IV ivory	BL black
AL almond	

colors (gloss finish) (see page 12 for color swatches)

WH white	LA light almond
IV ivory	BL black
AL almond	

colors (metal finish) (see page 12 for color swatch)

SS stainless steel
