

NL-3318

3" Adjustable Eyeball with Baffle

FEATURES

Trim: Metal trim with adjustable eyeball can be rotated 358° horizontally and 10° vertically. Precision spun 0.040 aluminum baffle with deep grooves to reduce aperture glare. Gimbal ring allows lamp to be mounted on top of the trim. Separate trim ring available in custom combination of ring finishes (consult factory).

Mounting: Trim includes three trim clips that securely mount trim in housing.

COMPATIBLE HOUSINGS

Compatible with Line Voltage and Low Voltage housings. See individual specification sheets for more information.

LAMP

Line Voltage

50W 120V MR16 GU10 Max. (NH-350AT; NHIC-350AT; NHR-354AT)

Low Voltage

Important: Do not use glass lens (provided) when already using lamp with glass cover
50W 12V MR16 (NL-301 Series; NLIC-301 Series; NLR-304 Series; NLR-305 Series)

LABELS AND LISTINGS

cULus Listed for Damp Location when used with compatible housing.



Type

Project


Catalog No.

Notes

Product Images and Dimensions



NL-3318N
Black Baffle
Natural Metal Trim



3" Adjustable Eyeball with Baffle

Catalog No.

NL-3318N = Black Baffle and Natural Metal Trim

Compatible Housings

Line Voltage

Catalog No.

NH-350AT = 3" Non-IC Air-Tight New Construction Housing / 50W max.

NHIC-350AT = 3" IC Air-Tight New Construction Housing / 50W max.

NHR-354AT = 3" Non-IC Air-Tight Remodel Housing / 50W max.

Low Voltage

Catalog No.

NLIC-301AT/1EL = 3" IC Air-Tight New Construction Housing / 50W max.

NLIC-3010AT/20 = 3" IC Air-Tight New Construction Housing / 20W max.

NLIC-3010AT/37 = 3" IC Air-Tight New Construction Housing / 37W max.

NLIC-3010AT = 3" IC Air-Tight New Construction Housing / 50W max.

NL-301AT/1EL = 3" Non-IC Air-Tight New Const. Housing / 50W max.

NL-3010AT/20 = 3" Non-IC Air-Tight New Const. Housing / 20W max.

NL-3010AT/37 = 3" Non-IC Air-Tight New Const. Housing / 37W max.

NL-3010AT = 3" Non-IC Air-Tight New Const. Housing / 50W max.

NLR-304AT/1EL = 3" Non-IC Air-Tight Remodel Housing / 50W max.

NLR-3040AT/20 = 3" Non-IC Air-Tight Remodel Housing / 20W max.

NLR-3040AT/37 = 3" Non-IC Air-Tight Remodel Housing / 37W max.

NLR-3040AT = 3" Non-IC Air-Tight Remodel Housing / 50W max.

NLR-305AT/20 = 3" Non-IC Air-Tight Remodel Housing / 20W max.

NLR-305AT/37 = 3" Non-IC Air-Tight Remodel Housing / 37W max.

NLR-305AT = 3" Non-IC Air-Tight Remodel Housing / 50W max.

Example: **NL-3318N** = 3" Adjustable Eyeball with Baffle, Black Baffle and Natural Metal Trim