

NL-3345

3" Adjustable Slot Aperture

FEATURES

Trim: Metal trim with 1-1/8" x 1-3/4" slot aperture that can rotate 358° horizontally. Gimbal ring allows lamp to be mounted on top of the trim and adjustable up to 35°. Separate trim ring available in custom combination of ring finishes (consult factory).

Mounting: Trim includes three trim clips that securely mount trim in housing.

COMPATIBLE HOUSINGS

Compatible with Line Voltage and Low Voltage housings. See individual specification sheets for more information.

LAMP

Line Voltage

50W 120V MR16 GU10 Max. (NH-350AT; NHIC-350AT; NHR-354AT)

Low Voltage

Important: Do not use glass lens (provided) when already using lamp with glass cover
50W 12V MR16 (NL-301 Series; NLIC-301 Series; NLR-304 Series; NLR-305 Series)

LABELS AND LISTINGS

cULus Listed for Damp Location when used with compatible housing.



Type

Project


Catalog No.

Notes

Product Images and Dimensions



NL-3345W
White Ring



3" Adjustable Slot Aperture

Catalog No.

NL-3345W = Adjustable Slot Aperture, White Trim

Compatible Housings

Line Voltage

Catalog No.

NH-350AT = 3" Non-IC Air-Tight New Construction Housing / 50W max.

NHIC-350AT = 3" IC Air-Tight New Construction Housing / 50W max.

NHR-354AT = 3" Non-IC Air-Tight Remodel Housing / 50W max.

Low Voltage

Catalog No.

NLIC-301AT/1EL = 3" IC Air-Tight New Construction Housing / 50W max.

NLIC-3010AT/20 = 3" IC Air-Tight New Construction Housing / 20W max.

NLIC-3010AT/37 = 3" IC Air-Tight New Construction Housing / 37W max.

NLIC-3010AT = 3" IC Air-Tight New Construction Housing / 50W max.

NL-301AT/1EL = 3" Non-IC Air-Tight New Const. Housing / 50W max.

NL-3010AT/20 = 3" Non-IC Air-Tight New Const. Housing / 20W max.

NL-3010AT/37 = 3" Non-IC Air-Tight New Const. Housing / 37W max.

NL-3010AT = 3" Non-IC Air-Tight New Const. Housing / 50W max.

NLR-304AT/1EL = 3" Non-IC Air-Tight Remodel Housing / 50W max.

NLR-3040AT/20 = 3" Non-IC Air-Tight Remodel Housing / 20W max.

NLR-3040AT/37 = 3" Non-IC Air-Tight Remodel Housing / 37W max.

NLR-3040AT = 3" Non-IC Air-Tight Remodel Housing / 50W max.

NLR-305AT/20 = 3" Non-IC Air-Tight Remodel Housing / 20W max.

NLR-305AT/37 = 3" Non-IC Air-Tight Remodel Housing / 37W max.

NLR-305AT = 3" Non-IC Air-Tight Remodel Housing / 50W max.

Example: **NL-3345W** = 3" Adjustable Slot Aperture, White Trim