

NL-3412

3" Square Reflector with Round Aperture

Type

Project

Catalog No.

Notes

FEATURES

Trim: Precision spun 0.050 aluminum high grade reflector. Gimbal ring allows lamp to be mounted on top of the trim and adjustable up to 35°.

Mounting: Trim includes three trim clips that securely mount trim in housing.

COMPATIBLE HOUSINGS

Compatible with Line Voltage and Low Voltage housings. See individual specification sheets for more information.

COMPATIBLE LAMP / HOUSINGS

Low Voltage:

Important: Do not use glass lens (provided) when already using lamp with glass cover
50W 12V MR16 (NL-301 Series; NLIC-301 Series; NLR-304 Series; NLR-305 Series)

Line Voltage:

50W 120V MR16 GU10 Max. (NH-350AT; NHIC-350AT; NHR-354AT)

LABELS AND LISTINGS

cULus Listed for Damp Location when used with compatible housing.




Product Images and Dimensions



NL-3412WW

Specular White Reflector
White Trim



3" Square Reflector with Round Aperture

Catalog No.

NL-3412WW = Specular White Reflector / White Trim

Compatible Housings

Line Voltage

Catalog No.

NH-350AT = 3" Non-IC Air-Tight New Construction Housing / 50W max.

NHIC-350AT = 3" IC Air-Tight New Construction Housing / 50W max.

NHR-354AT = 3" Non-IC Air-Tight Remodel Housing / 50W max.

Low Voltage

Catalog No.

NLIC-301AT/1EL = 3" IC Air-Tight New Construction Housing / 50W max.

NLIC-301QAT/20 = 3" IC Air-Tight New Construction Housing / 20W max.

NLIC-301QAT/37 = 3" IC Air-Tight New Construction Housing / 37W max.

NLIC-301QAT = 3" IC Air-Tight New Construction Housing / 50W max.

NL-301AT/1EL = 3" Non-IC Air-Tight New Const. Housing / 50W max.

NL-301QAT/20 = 3" Non-IC Air-Tight New Const. Housing / 20W max.

NL-301QAT/37 = 3" Non-IC Air-Tight New Const. Housing / 37W max.

NL-301QAT = 3" Non-IC Air-Tight New Const. Housing / 50W max.

NLR-304AT/1EL = 3" Non-IC Air-Tight Remodel Housing / 50W max.

NLR-304QAT/20 = 3" Non-IC Air-Tight Remodel Housing / 20W max.

NLR-304QAT/37 = 3" Non-IC Air-Tight Remodel Housing / 37W max.

NLR-304QAT = 3" Non-IC Air-Tight Remodel Housing / 50W max.

NLR-305AT/20 = 3" Non-IC Air-Tight Remodel Housing / 20W max.

NLR-305AT/37 = 3" Non-IC Air-Tight Remodel Housing / 37W max.

NLR-305AT = 3" Non-IC Air-Tight Remodel Housing / 50W max.

Example: **NL-3412WW** = 3" Square Reflector with Round Aperture, Specular White Reflector / White Trim