

NL-413 / NL-414 / NL-416 / NL-452 / NL-453

4" Round Adjustable Reflector

Type

Project

Catalog No.

Notes

FEATURES

Trim: Precision spun 0.050 aluminum high grade reflector. Gimbal ring allows lamp to be mounted on top of the trim and adjustable up to 35°. Separate trim ring available in metal, may also be used with custom combination of plastic or metal ring finishes.

Mounting: Trim includes three trim clips that securely mount trim in housing.

COMPATIBLE HOUSINGS

Compatible with Line Voltage and Low Voltage housings. See individual specification sheets for more information.

LABELS AND LISTINGS

cULus Listed for Damp Location when used with compatible housing.



COMPATIBLE LAMP / HOUSINGS

Low Voltage:


20W MR16 max. (NL-401QAT/20; NLIC-401QSAT/20; NLR-404QAT/20; NLR-405AT/20; NLIC-402SAT/20; NL-402S/20; NLR-403S/20)
 37W MR16 max. (NL-401QAT/37; NLIC-401QSAT/37; NLR-404QAT/37; NLR-405AT/37; NLIC-402QSAT/37; NL-402S/37; NLR-403S/37)
 50W MR16 max. (NLIC-401AT/1EL; NLIC-401AT/2EL; NLIC-401QSAT; NL-401AT/1EL; NL-401QAT; NLR-404AT/1EL; NLR-404AT/2EL; NLR-404QAT; NLR-405AT; NLIC-402AT/1EL; NLIC-402QSAT; NL-402S/1EL; NL-402S; NLR-403S/1EL; NLR-403S)
 75W MR16 max. (NL-401/75/1EL; NLR-404/75/1EL; NLR-404/75/2EL; NLR-404/75)

Line Voltage:

20W MR16 max. (NSEIC-407AT/20; NSERIC-407AT/20)
 25W MR16 max. (NFBIC-401AT/25A)
 50W MR16 GU10 max. (NSL-401AT/10; NSLIC-401AT/10; NSLR-404AT/10)

IMPORTANT: DO NOT USE GLASS LENS WHEN ALREADY USING LAMP W/ GLASS COVER

Product Dimensions



Compatible Housings

Catalog No.

Low Voltage

- NLIC-401QSAT/20 = ICAT New Construction / 120V Magnetic / 20W max.
- NLIC-401QSAT/37 = ICAT New Construction / 120V Magnetic / 37W max.
- NLIC-401QSAT = ICAT New Construction / 120V Magnetic / 50W max.
- NLIC-401AT/1EL = ICAT New Construction / 120V Electronic / 50W max.
- NLIC-401AT/2EL = ICAT New Construction / 120V Electronic / 50W max.
- NL-401QAT/20 = Non-IC AT New Construction / 120V Magnetic / 20W max.
- NL-401QAT/37 = Non-IC AT New Construction / 120V Magnetic / 37W max.
- NL-401QAT = Non-IC AT New Construction / 120V Magnetic / 50W max.
- NL-401AT/1EL = Non-IC AT New Construction / 120V Electronic / 50W max.
- NL-401/75/1EL = Non-IC New Construction / 120V Electronic / 75W max.
- NLIC-402QSAT/20 = ICAT Shallow New Construction / 120V Magnetic / 20W max.
- NLIC-402QSAT/37 = ICAT Shallow New Construction / 120V Magnetic / 37W max.
- NLIC-402QSAT = ICAT Shallow New Construction / 120V Magnetic / 50W max.
- NLIC-402AT/1EL = ICAT Shallow New Construction / 120V Electronic / 50W max.
- NL-402S/20 = Non-IC Shallow New Construction / 120V Magnetic / 20W max.
- NL-402S/37 = Non-IC Shallow New Construction / 120V Magnetic / 37W max.
- NL-402S = Non-IC Shallow New Construction / 120V Magnetic / 50W max.
- NL-402S/1EL = Non-IC Shallow New Construction / 120V Electronic / 50W max.
- NLR-403S/20 = Non-IC Shallow Remodel / 120V Magnetic / 20W max.
- NLR-403S/37 = Non-IC Shallow Remodel / 120V Magnetic / 37W max.
- NLR-403S = Non-IC Shallow Remodel / 120V Magnetic / 50W max.
- NLR-403S/1EL = Non-IC Shallow Remodel / 120V Electronic / 50W max.
- NLR-404QAT/20 = Non-IC AT Remodel / 120V Magnetic / 20W max.
- NLR-404QAT/37 = Non-IC AT Remodel / 120V Magnetic / 37W max.
- NLR-404QAT = Non-IC AT Remodel / 120V Magnetic / 50W max.
- NLR-404/75 = Non-IC Remodel / 120V Magnetic / 75W max.
- NLR-404AT/1EL = Non-IC AT Remodel / 120V Electronic / 50W max.
- NLR-404AT/2EL = Non-IC AT Remodel / 277V Electronic / 50W max.
- NLR-404/75/1EL = Non-IC Remodel / 120V Electronic / 75W max.
- NLR-404/75/2EL = Non-IC Remodel / 277V Electronic / 75W max.
- NLR-405AT/20 = Non-IC AT Remodel / No Transformer / 20W max.
- NLR-405AT/37 = Non-IC AT Remodel / No Transformer / 37W max.
- NLR-405AT = Non-IC AT Remodel / No Transformer / 50W max.

Line Voltage

- NSEIC-407AT/20 = ICAT LED New Construction / 20W
- NSERIC-407AT/20 = ICAT LED Remodel / 20W
- NFBIC-401AT/25A = Fire Rated IC Air-Tight New Construction / 25W
- NSLIC-401AT/10 = ICAT New Construction / 50W
- NSL-401AT/10 = Non-IC Air-Tight New Construction / 50W
- NSLR-404AT/10 = Non-IC Air-Tight Remodel / 50W

Product Images



NL-413
Specular Black Reflector
White Trim



NL-414
Specular Clear Reflector
White Trim



NL-414HZ
Haze Reflector
White Trim



NL-416
Specular White Reflector
White Trim



NL-452
Natural Metal Reflector
Natural Metal Trim



NL-453
Copper Reflector
Copper Trim



NL-453BZ
Bronze Reflector
Bronze Trim

4" Round Adjustable Reflector

Catalog No.

- NL-413 = Specular Black Reflector with White Metal Trim
- NL-414 = Specular Clear Reflector with White Metal Trim
- NL-414HZ = Haze Reflector with White Metal Trim
- NL-416 = White Reflector with White Metal Trim
- NL-452 = Natural Metal Reflector with Natural Metal Trim
- NL-453 = Copper Reflector with Copper Metal Trim
- NL-453BZ = Bronze Reflector with Bronze Metal Trim

Example: NL-414HZ = 4" Round Haze Reflector with White Metal Trim