

NL-432

4" Round Deep Reflector

Type

Project

Catalog No.

Notes

FEATURES

Trim: Deep cone reflector offers very low aperture brightness. 55° visual cut-off to lamp and lamp image. Special design on reflector to trim ring with no halo / ring brightness. Precision spun 0.050 aluminum high grade reflector.

Mounting: Trim includes three trim clips that securely mount trim in housing.

COMPATIBLE HOUSINGS

Compatible with Line Voltage and Low Voltage housings. See individual specification sheets for more information.

COMPATIBLE LAMP / HOUSINGS

Low Voltage:

20W MR16 max. (NL-401QAT/20; NLIC-401QSAT/20; NLR-404QAT/20; NLR-405AT/20)
37W MR16 max. (NL-401QAT/37; NLIC-401QSAT/37; NLR-404QAT/37; NLR-405AT/37)
50W MR16 max. (NLIC-401AT/1EL; NLIC-401AT/2EL; NLIC-401QSAT; NL-401AT/1EL; NL-401QAT; NLR-404AT/1EL; NLR-404AT/2EL; NLR-404QAT; NLR-405AT)
75W MR16 max. (NL-401/75/1EL; NLR-404/75/1EL; NLR-404/75/2EL; NLR-404/75)

Line Voltage:

20W MR16 max. (NSEIC-407AT/20; NSERIC-407AT/20)
25W MR16 max. (NFBIC-401AT/25A)
50W MR16 GU10 max. (NSL-401AT/10; NSLIC-401AT/10; NSLR-404AT/10)

IMPORTANT: DO NOT USE GLASS LENS WHEN ALREADY USING LAMP W/ GLASS COVER

LABELS AND LISTINGS

cULus Listed for Damp Location when used with compatible housing.



Product Image and Dimensions




NL-432BZ
Bronze Reflector
Bronze Trim



NL-432HZW
Haze Reflector
White Trim



NL-432WW
Specular White Reflector
White Trim



Compatible Housings

Catalog No.

Low Voltage

- NLIC-401QSAT/20** = ICAT New Construction / 120V Magnetic / 20W
- NLIC-401QSAT/37** = ICAT New Construction / 120V Magnetic / 37W
- NLIC-401QSAT** = ICAT New Construction / 120V Magnetic / 50W
- NLIC-401AT/1EL** = ICAT New Construction / 120V Electronic / 50W
- NLIC-401AT/2EL** = ICAT New Construction / 120V Electronic / 50W
- NL-401QAT/20** = Non-IC AT New Construction / 120V Magnetic / 20W
- NL-401QAT/37** = Non-IC AT New Construction / 120V Magnetic / 37W
- NL-401QAT** = Non-IC AT New Construction / 120V Magnetic / 50W
- NL-401AT/1EL** = Non-IC AT New Construction / 120V Electronic / 50W
- NL-401/75/1EL** = Non-IC New Construction / 120V Electronic / 75W
- NLR-404QAT/20** = Non-IC AT Remodel / 120V Magnetic / 20W
- NLR-404QAT/37** = Non-IC AT Remodel / 120V Magnetic / 37W
- NLR-404QAT** = Non-IC AT Remodel / 120V Magnetic / 50W
- NLR-404/75** = Non-IC Remodel / 120V Magnetic / 75W
- NLR-404AT/1EL** = Non-IC AT Remodel / 120V Electronic / 50W
- NLR-404AT/2EL** = Non-IC AT Remodel / 277V Electronic / 50W
- NLR-404/75/1EL** = Non-IC Remodel / 120V Electronic / 75W
- NLR-404/75/2EL** = Non-IC Remodel / 277V Electronic / 75W
- NLR-405AT/20** = Non-IC AT Remodel / No Transformer / 20W
- NLR-405AT/37** = Non-IC AT Remodel / No Transformer / 37W
- NLR-405AT** = Non-IC AT Remodel / No Transformer / 50W

Line Voltage

- NSEIC-407AT/20** = ICAT LED New Construction / 20W
- NSERIC-407AT/20** = ICAT LED Remodel / 20W
- NFBIC-401AT/25A** = Fire Rated IC Air-Tight New Construction / 25W
- NSLIC-401AT/10** = ICAT New Construction / 50W
- NSL-401AT/10** = Non-IC Air-Tight New Construction / 50W
- NSLR-404AT/10** = Non-IC Air-Tight Remodel / 50W

4" Round Deep Reflector

Catalog No.

- NL-432BZ** = Bronze Reflector with Bronze Trim
- NL-432HZW** = Haze Reflector with White Trim
- NL-432WW** = Specular White Reflector with White Trim

Example: **NL-432WW** = 4" Round Specular White Reflector with White Trim