

NLR-409AT

Q4 Series

4" Square Air-Tight Low Voltage Remodel Housing

Source: 50W MR16 max.

Type

Project

Catalog No.

Notes

PRODUCT DESCRIPTION

The square housings feature die formed steel black painted housings. The Q4 is available with magnetic or electronic transformers. Reflectors feature deep set lamp holders for maximum visual comfort. Air-tight construction provides energy savings by reducing the flow of air through the ceiling

FEATURES

- Air-Tight energy saving by reducing the flow of air through the ceiling
- Internal thermal protection
- cULus listed for damp locations and through branch circuit wiring
- Quick connect provided

CONSTRUCTION

Housing: Aluminum housing terminates at a 1/4" ceiling flange for even positioning of housing angle within the ceiling. Structural arm consists of 0.05 steel and connects to housing with junction box.

Minimum Clearance: Non-IC housings require a minimum clearance of 3" from thermal insulation and 1/2" from adjacent building components.

Air Flow Restriction: Housing has factory installed gaskets to restrict airflow from room into ceiling plenum to <2CFM (cubic feet per minute) in accordance with ASTM-283 Air-Tight requirements.

Mounting: Four high tension tempered steel springs secure remodel housing to ceiling. (Hole cutout template provided for convenience).

Junction Box: Prewired 15 cubic inch 0.060" thick galvanized steel, with six 1/2" knockouts, four Romex® pryouts, and snap on cover. All leads are #18AWG wire, the ground wire is connected to the bottom, and quick connectors are supplied on all leads. Through branch circuit wiring, (4-in, 4-out).

Transformer:

Electronic: Thermally protected, single tap input voltage available in 12V 60Hz with short circuit protection. Approved for use with LED lamps.

Magnetic: Thermally protected, single tap input voltage available in 12V 60Hz. Class H.

ELECTRICAL

Input Voltage: 120V

Output Voltage: 12V

Socket: Bi-Pin GU5.3 socket with heat shield

Wattage: 50W max.

Lamp: MR16 (not included)

Transformer: Electronic or Magnetic (must specify)

COMPATIBLE TRIM

NL-4585WW - Reflector with Adjustable Gimbal

OPTIONAL ACCESSORIES



NRA-36N - Replacement socket with heat shield

LABELS AND LISTINGS

- cULus Listed for Damp Locations w/ Feed Through
- Meets or exceeds ASTM-283 Air-Tight Requirements



PRODUCT IMAGES & DIMENSIONS



4" Square Air-Tight Low Voltage Remodel Housing

Catalog No.

NLR-409AT = 4" Square Air-Tight Low Voltage Remodel Housing, 120V Magnetic, 50W max.

NLR-409AT/20 = 4" Square Air-Tight Low Voltage Remodel Housing, 120V Magnetic, Labeled 20W max.

NLR-409AT/37 = 4" Square Air-Tight Low Voltage Remodel Housing, 120V Magnetic, Labeled 37W max.

NLR-409AT/IEL = 4" Square IC Air-Tight Low Voltage Remodel Housing, 120V Electronic, 3W-50W (use with EMI filter for FCC Class B compliance)

Optional Accessories

Catalog No.

NRA-36N = Replacement socket with heat shield

Example: **NLR-409AT** = 4" Square Air-Tight Low Voltage Remodel Housing, 120V Magnetic, 50W max.