# NMRT-1

Flanged Gimbal Comfort Dim LED Multiple Lighting Trim (Housing Required)

Source: 11W to 37W LED

850lm to 3000lm per head

# Type **Project** Catalog No. **Notes**

#### PRODUCT DESCRIPTION

A beautiful enclosed steel face plate. Gimbal regressed 1.5 inch for a clean ceiling appearance. Available in 1, 2 and 3 LED linear configurations. Excellent for flexible general lighting in commercial and architectural applications.

Trim: The aluminum face plate is a flanged seamless stamped metal. Each LED gimbal adjusts independently at 40° with 350° rotation.

**Mounting:** Trim includes two "V" torsion springs to mount trim securely to housing.

Trim Style: Trim is available in two styles; 1-1/2" regressed or flat face. Flat face is only available in white finish.

Finish: Flange is available in silver or white finish. Regressed face is available in black, silver or white finish.

**ELECTRICAL** 

Input Voltage: 120V or 277V

**Lumens / Wattage: L85** = 850lm / 11W; **L20** = 2000lm / 25W; **L30** = 3000lm / 37W

CRI: 90+CRI

**Operating Temp.:** 0°C to 45°C ambient temperature

Comfort Dim: Comfort Dim color tunes the temperature from a bright 2700K, to a romantic and comfortable 1800K on a gradual,

even curve.

Comfort Dim is available in 4 different lumen levels:

· 850 Lumens for lower ceiling heights in commercial and residential applications.

- · 2000 Lumens for light commercial and residential high ceiling applications
- · 3000 Lumens for commercial high ceiling applications

**Dimming:** ELV or 0-10V dimming

Click Here or check complete dimmer list at www.NoraLighting.com in the "Compatibility" page under "Resources" tab

#### **COMPATIBLE LED HOUSING**

Catalog No. Description

NMRG-1 Flanged Gimbal Comfort Dim LED Housing

### **LABELS AND LISTINGS**

- · cULus Listed for damp locations
- · ENERGY STAR certified
- · 5-Year Limited Warranty
















#### PRODUCT IMAGES AND DIMENSIONS





Dimensions	Length (A)
1 Head	9-3/4"
2 Head	18"
3 Head	23-3/4"

## Flanged Gimbal Comfort Dim LED Multiple Lighting Trim - Housing ordered separately

Face Type	Number of Heads	Lumens / Wattage Per Head	Color Temp.	Face / Flange Finish
NMRT-1 = Regressed Face	1 = One Head	<b>L85</b> = 850lm / 11W	<b>CD</b> = Comfort Dim	BW = Black / White
NMRT-1F = Flat Face*	2 = Two Heads	<b>L20</b> = 2000lm / 25W		SS = Silver / Silver
	3 = Three Heads	<b>L30</b> = 3000lm / 37W		WW = White / White

<sup>\*</sup> Flat face available in White / White finish only

Example: NMRT-12L20CDBW = Two Head Regressed Face Flanged Gimbal Comfort Dim LED Multiple Lighting Trim, 2000lm / 25W per head, Black Face / White Flange

