

# NMRT2

## Flanged High Lumen LED Gimbal Multiple Lighting Trim

Source: 16W to 27W LED

900lm to 2500lm per head

Type

Project

Catalog No.

Notes

### PRODUCT DESCRIPTION

A beautiful enclosed steel face plate. Gimbal regressed 1.5 inch for a clean ceiling appearance. Available in 1, 2 and 3 LED linear configurations. Excellent for flexible general lighting in commercial and architectural applications.

### CONSTRUCTION

**Trim:** The aluminum face plate is a flanged seamless stamped metal. Each LED gimbal adjusts independently at 40° with 350° rotation.

**Mounting:** Trim includes two "V" torsion springs to mount trim securely to housing.

**Trim Style:** Trim is available in two styles; 1-1/2" regressed or flat face. Flat face is only available in white finish.

**Finish:** Flange is available in silver or white finish. Regressed face is available in black, silver or white finish.

### ELECTRICAL

**Input Voltage:** 120V or 120-277V (must specify)

**Lumens / Wattage:** **L09** = 900lm / 16W; **L15** = 1500lm / 18W; **L25** = 2500lm / 27W

**Color Temperature:** 2700K, 3000K, 3500K or 4000K

**Color Rendering Index:** 90+CRI

**Beam Spread:** **(S)** 45° Spot, **(M)** 64° Narrow Flood, **(F)** 79° Flood

**Operating Temperature:** 0°C to 45°C

**Dimming:** Triac, ELV or 0-10V dimming (must specify)

[Click Here](#) or check complete dimmer list at [www.NoraLighting.com](http://www.NoraLighting.com) in the "Compatibility" page under "Resources" tab

### COMPATIBLE HOUSINGS


CATALOG NO.	DESCRIPTION
<a href="#">NMRG2-11</a>	One-Head Housing
<a href="#">NMRG2-12</a>	Two-Head Housing
<a href="#">NMRG2-13</a>	Three-Head Housing

### LABELS AND LISTINGS

- cULus Listed for damp locations
- ENERGY STAR certified
- 5-Year Limited Warranty



### PRODUCT IMAGES AND DIMENSIONS



Dimensions	Length (A)
1 Head	9-3/4"
2 Head	18"
3 Head	23-3/4"

## Flanged High Lumen LED Gimbal Multiple Lighting Trim

Face Type	Number of Heads	Lumens / Wattage Per Head	Color Temperature	Beam Spread	Face / Flange Finish
<b>NMRT2-1</b> = Regressed Face	<b>1</b> = One Head	<b>L09</b> = 900lm / 16W	<b>27</b> = 2700K	<b>S</b> = 45° Spot	<b>BW</b> = Black / White
<b>NMRT2-1F</b> = Flat Face*	<b>2</b> = Two Heads	<b>L15</b> = 1500lm / 18W	<b>30</b> = 3000K	<b>M</b> = 64° Narrow Flood	<b>SS</b> = Silver / Silver
	<b>3</b> = Three Heads	<b>L25</b> = 2500lm / 27W	<b>35</b> = 3500K	<b>F</b> = 79° Flood	<b>WW</b> = White / White
			<b>40</b> = 4000K		

\*Flat face available in White/White finish only.

Example: **NMRT2-12L2530SBW** = Two Head Regressed Face Flanged High Lumen LED Gimbal Multiple Lighting Trim, 2500lm / 27W per head, 3000K, 45° Spot, Black Face / White Flange