

NMT-48/24C2D1

24V Dimmable Class II Hardwire Magnetic Driver

Source: 120V Input / 24V Output
48W

Type
Project
Catalog No.
Notes

PRODUCT DESCRIPTION

24V enclosed dimmable driver to be used with Nora Lighting's 24 Volt systems requiring a Class II driver. Produces 48 watts and can be dimmed with low voltage magnetic dimmer. Includes a regulator to provide constant current and constant voltage.

FEATURES

- Fully dimmable with low voltage magnetic dimming
- Integral regulator for constant current and voltage
- Manual Reset Overload Protection for each Class II Circuit
- Indoor/Outdoor Enclosure Type 3R Enclosure
- Conduit Access Wiring Compartment
- Made in USA
- Meets Class II output limits
- 24 Volt DC Rated output
- cULus Listed & CSA approved

ELECTRICAL

Input Voltage: 120V

Output Voltage: 24VDC, 2A max.

Wattage: 48W

Dimming: Magnetic Low Voltage

Regulator: Constant Current and Constant Voltage

COMPATIBLE NORA 12V SYSTEMS

LED Drivers are compatible with Nora Lighting's 24V systems

SERIES	DESCRIPTION
NMP2-A	24V Josh Adjustable
NMP2-LED	24V Josh Fixed
NUTP1	24V Standard Tape Light (Silicone Encapsulated)
NUTP3	24V RGB Color Changing Tape Light
NUTP5	24V Hy-Brite Tape Light
NUTP7	24V Standard Tape Light (Non-Encapsulated)
NUTP8	24V High Output Tape Light
NUTP9	24V Side-Lit Tape Light
NUTP10	24V CCT Color Changing Tape Light
NUTP11	24V RGBW Color Changing Tape Light
NUTP12	24V Comfort Dim (warm dim) Tape Light
NUTP51	24V Continuous Hy-Brite Tape Light
NUTP71	24V Continuous Standard Tape Light
NUTP81	24V Continuous High Output Tape Light
NULB	24V Lightbar Silk SBC

OPTIONAL ACCESSORIES

NALTL-10: 10' Power Line Connector

NALTL-30: 30' Power Line Connector


NATL-302W: Power Line Splitter, white cable. Splits power line connector into two separate connections.

LABELS AND LISTINGS

- Three Year Limited Warranty
- cULus Listed
- CSA approved



PRODUCT IMAGES & DIMENSIONS



NMT-48/24C2D1

24V Dimmable Class II Hardwire LED Driver
MLV dimming



NALTL-10 / NALTL-30

Power Line Connector



NATL-302W

Power Line Splitter

24V Dimmable Class II Hardwire Magnetic Driver

Output Voltage / Wattage
NMT-48/24C2D1 = 24V Duput / 48W

Optional Accessories

Description
NALTL-10 = 10' Power Line Connector
NALTL-30 = 30' Power Line Connector
NATL-302W = Power Line Splitter, White

Example: **NMT-48/24C2D1** = 24V 48W Dimmable Class II Hardwire Magnetic Driver