

NP-26

6" Frosted Flat Lens with Plastic Trim

Type _____

Project _____

Catalog No. _____

Notes _____

FEATURES

Trim: High grade frosted flat lens attached to plastic trim.

Mounting: Trim includes two "V" torsion springs to mount trim securely to housing. Replacement "V" torsion springs are available (NRA-86).

COMPATIBLE LAMP / HOUSINGS

Line Voltage:

25W A19 max. (NHIC-27QAT; NHRIC-27QAT)

40W A19 max. (NHIC-17QAT; NHIC-926QAT; NHRIC-17QAT; NHRIC-926QAT)

60W A19 max. (NH-26Q; NH-27Q; NHIC-17/100DWQA; NHR-26Q; NHR-27Q)

See individual housing specification sheets for more information.

RATING


Rated for Wet Location when used with compatible housing



PRODUCT IMAGES & DIMENSIONS



NP-26



6" Frosted Flat Lens with Plastic Trim

Catalog No.

NP-26 = 6" Frosted Flat Lens with White Plastic Trim

Compatible Housings

Catalog No.

NH-26Q = Non-IC New Construction / 60W max.

NHR-26Q = Non-IC Remodel / 60W max.

NHIC-17/100DWQA = IC Air-Tight Double Wall New Construction / 60W max.

NHIC-17QAT = IC Air-Tight New Construction / 40W max.

NHRIC-17QAT = IC Air-Tight Remodel / 40W max.

NH-27Q = Shallow Non-IC New Construction / 60W max.

NHR-27Q = Shallow Non-IC Remodel / 60W max.

NHIC-27QAT = Shallow IC Air-Tight New Construction / 25W max.

NHRIC-27QAT = Shallow IC Air-Tight Remodel / 25W max.

NHIC-926QAT = Sloped IC Air-Tight New Construction / 40W max.

NHRIC-926QAT = Sloped IC Air-Tight Remodel / 40W max.

Example: NP-26 = 6" Frosted Flat Lens with White Plastic Trim