

NTM-323 / NP-323

6" Fresnel Lens with Trim and Bracket

Type _____

Project _____

Catalog No. _____

Notes _____

FEATURES

Trim: High grade fresnel lens attached to a plastic or metal trim with a bracket.

Mounting: Trim includes two "V" torsion springs to mount trim securely to housing. Replacement "V" torsion springs are available (NRA-86). Remove socket from socket plate within housing (if applicable), and mount lamp into gimbal ring.

COMPATIBLE HOUSINGS

Compatible with line voltage housings. See individual specification sheets for more information.

LAMP

- 25W A19 Max. (NHIC-270AT; NHRIC-270AT)
- 40W A19 Max. (NHIC-170AT; NHIC-170NBAT; NHRIC-170AT; NHRIC-170NBAT)
- 60W A19 Maximum (NH-260; NH-270; NHIC-17/100DWQA; NHR-260; NHR-270)

LABELS AND LISTINGS

- cULus Listed for Wet Location when used with compatible housing.




PRODUCT IMAGES AND DIMENSIONS



NTM-323B



NP-323



6" Fresnel Lens with Trim and Bracket

Catalog No. _____

NP-323 = 6" Fresnel Lens with White Plastic Trim and Bracket

NTM-323B = 6" Fresnel Lens with Black Metal Trim and Bracket

Compatible Housings

Catalog No. _____

- NHIC-270AT** = IC Air-Tight Shallow New Construction / 25W max
- NHRIC-270AT** = IC Air-Tight Shallow Remodel / 25W max
- NHIC-170AT** = IC Air-Tight New Construction / 40W
- NHIC-170NBAT** = 6" IC Air-Tight New Construction, No Bracket / 40W
- NHRIC-170AT** = IC Air-Tight Line Voltage Remodel / 40W max
- NHRIC-170NBAT** = IC Air-Tight Remodel, No Bracket / 40W max
- NH-260** = Non-IC New Construction / 60W max
- NH-270** = Non-IC Shallow New Construction / 60W max
- NHIC-17/100DWQA** = IC Air-Tight Double Wall New Construction / 60W max
- NHR-260** = Non-IC Remodel / 60W max
- NHR-270** = 6" Non-IC Shallow Remodel / 60W max

Example: **NTM-323B** = 6" Fresnel Lens with Black Metal Trim and Bracket