

NS-18

4" Adjustable Eyeball

Type _____

Project _____

Catalog No. _____

Notes _____

FEATURES

Trim: Metal trim with adjustable eyeball can be rotated 358° horizontally and 15° vertically. Eyeball allows lamp to be mounted inside and adjust with trim.

Mounting: Trim includes three trim clips that securely mount trim in housing. Remove socket from plate and mount directly onto eyeball.

COMPATIBLE LAMP / HOUSINGS

Line Voltage:

15W R20/PAR20 max. (NS-401AT/IC)

35W R20/PAR20 max. (NFBIC-4INCATA)

50W R20/PAR20 max. (NS-401QAT; NSIC-401QAT; NSR-404QAT; NSRIC-404QAT)

See individual housing specification sheets for more information.

LABELS AND LISTINGS

* cULus Listed for Damp Location when used with compatible housing



PRODUCT IMAGES & DIMENSIONS




NS-18



NS-18B



NS-18BZ



4" Surface Gimbal Ring

Catalog No.

NS-18 = 4" White Adjustable Eyeball

NS-18B = 4" Black Adjustable Eyeball

NS-18BZ = 4" Bronze Adjustable Eyeball

Compatible Housings

Catalog No.

NFBIC-4INCATA = 2-Hour Fire Rated New Construction / 35W max.

NS-401QAT = Non-IC Air-Tight New Construction / 50W max

NS-401QAT/IC = IC Air-Tight New Construction / 15W max

NSIC-401QAT = IC Air-Tight New Construction / 50W max

NSR-404QAT = Non-IC Air-Tight Remodel / 50W max

NSRIC-404QAT = IC Air-Tight Remodel / 50W max

Example: **NS-18** = 4" White Adjustable Eyeball