

NS-47

4" Adjustable Slot Aperture

Type _____

Project _____

Catalog No. _____

Notes _____

FEATURES

Trim: Metal trim with 1-3/8" x 2-1/4" slot aperture that can rotate 358° horizontally. Separate trim ring available in metal, may also be used with custom combination of plastic or metal ring finishes.

Mounting: Trim includes three trim clips that securely mount trim in housing.

COMPATIBLE LAMP / HOUSINGS

Line Voltage:

50W R20/PAR20 max. (NS-401QAT; NSIC-401QAT; NSR-404QAT; NSRIC-404QAT)

See individual housing specification sheets for more information.

LABELS AND LISTINGS


* cULus Listed for Damp Location when used with compatible housing



PRODUCT IMAGES & DIMENSIONS



NS-47



4" Adjustable Slot Aperture

Catalog No.

NS-47 = 4" White Adjustable Slot Aperture

Compatible Housings

Catalog No.

- NS-401QAT = Non-IC Air-Tight New Construction / 50W max
- NSIC-401QAT = IC Air-Tight New Construction / 50W max
- NSR-404QAT = Non-IC Air-Tight Remodel / 50W max
- NSRIC-404QAT = IC Air-Tight Remodel / 50W max

Example: NS-47 = 4" White Adjustable Slot Aperture