

# NS-4914

## 4" Reflector with Square Trim

Type \_\_\_\_\_

Project \_\_\_\_\_

Catalog No. \_\_\_\_\_

Notes \_\_\_\_\_

### FEATURES

**Trim:** 4" precision spun 0.050 aluminum high grade reflector. Non-reflective painted finishes and square trim.

**Mounting:** Trim includes three trim clips that securely mount trim in housing.

### COMPATIBLE LAMP / HOUSINGS

**Line Voltage:**

50W R20/PAR20 max. (NS-4010AT; NSIC-4010AT; NSR-4040AT; NSRIC-4040AT)

See individual housing specification sheets for more information.

### LABELS AND LISTINGS


\* cULus Listed for Damp Location when used with compatible housing



### PRODUCT IMAGES & DIMENSIONS



**NS-4914WW**



### 4" Reflector with Square Trim

Catalog No.

**NS-4914WW** = 4" Specular White Reflector with White Square Trim

### Compatible Housings

Catalog No.

- NS-4010AT** = Non-IC Air-Tight New Construction / 50W max
- NSIC-4010AT** = IC Air-Tight New Construction / 50W max
- NSR-4040AT** = Non-IC Air-Tight Remodel / 50W max
- NSRIC-4040AT** = IC Air-Tight Remodel / 50W max

Example: **NS-4912WW** = 4" White Surface Gimbal with White Square Trim