

# NS-76

## 4" Air-Tight Baffled Lensless Shower Trim

Type \_\_\_\_\_

Project \_\_\_\_\_

Catalog No. \_\_\_\_\_

Notes \_\_\_\_\_

### FEATURES

**Trim:** Precision spun 0.040 aluminum baffle with deep grooves to reduce aperture glare rated for wet location when used with compatible housings.

**Mounting:** Trim includes three trim clips that securely mount trim in housing.

### COMPATIBLE LAMP / HOUSINGS

**Line Voltage:**

35W R20/PAR20 max. (NFBIC-4INCATA)

50W R20/PAR20 max. (NS-401QAT; NSIC-401QAT; NSR-404QAT; NSRIC-404QAT)

See individual housing specification sheets for more information.

### LABELS AND LISTINGS

\* cULus Listed for Wet Location when used with compatible housing




### PRODUCT IMAGES & DIMENSIONS



NS-76BZ



NS-76W



### 4" Air-Tight Baffled Lensless Shower Trim

Catalog No.

**NS-76BZ** = 4" Bronze Air-Tight Baffled Lensless Trim

**NS-76W** = 4" White Air-Tight Baffled Lensless Trim

### Compatible Housings

Catalog No.

**NFBIC-4INCATA** = 2-Hour Fire Rated New Construction / 35W max.

**NS-401QAT** = Non-IC Air-Tight New Construction / 50W max

**NSIC-401QAT** = IC Air-Tight New Construction / 50W max

**NSR-404QAT** = Non-IC Air-Tight Remodel / 50W max

**NSRIC-404QAT** = IC Air-Tight Remodel / 50W max

Example: **NS-76W** = 4" White Air-Tight Baffled Lensless Trim