

NT-30

6" BR/PAR30 Open Metal Trim

Type _____

Project _____

Catalog No. _____

Notes _____

FEATURES

Trim: Metal trim with 3-7/8" open center.

Mounting: Trim includes two coil springs that clip and securely hold the trim into the housing when installed. Replacement coil springs are available (NRA-22).

COMPATIBLE LAMP / HOUSINGS

Line Voltage:

75W BR/PAR30 Maximum

(NH-260; NH-270; NHIC-17/100DWQA; NHIC-17QAT; NHIC-27QAT; NHR-260; NHR-270; NHRIC-17QAT; NHRIC-27QAT)

See individual housing specification sheets for more information.

LABELS AND LISTINGS

* cULus Listed for Damp Location when used with compatible housing

PRODUCT IMAGES & DIMENSIONS




NT-30



NT-30BZ



NT-30N



6" BR/PAR30 Open Metal Trim

Catalog No.

NT-30 = 6" Open Metal Trim, White

NT-30BZ = 6" Open Metal Trim, Bronze

NT-30N = 6" Open Metal Trim, Natural Metal

Compatible Housings

Catalog No.

NH-260 = Non-IC New Construction / 75W max

NH-270 = Shallow Non-IC New Construction / 75W max

NHIC-17/100DWQA = IC Double Wall Air-Tight New Const. / 75W max

NHIC-17QAT = IC Air-Tight New Construction / 75W max

NHIC-27QAT = Shallow IC Air-Tight New Construction / 75W max

NHR-260 = Non-IC Remodel / 75W max

NHR-270 = Shallow Non-IC Remodel / 75W max

NHRIC-17QAT = Shallow IC Air-Tight Remodel / 75W max

NHRIC-27QAT = Shallow IC Air-Tight Remodel / 75W max

Example: **NT-30** = 6" BR/PAR30 Open Metal Trim, White finish.