

NT-30D

6" BR/PAR30 Metal Splay Trim

Type _____

Project _____

Catalog No. _____

Notes _____

FEATURES

Trim: Metal splay trim with 3-7/8" open center.

Mounting: Trim includes two coil springs that clip and securely hold the trim into the housing when installed. Replacement coil springs are available (NRA-22).

COMPATIBLE LAMP / HOUSINGS

Line Voltage:

75W BR/PAR30 Maximum

(NH-260; NH-270; NHIC-17/100DWQA; NHIC-17QAT; NHIC-27QAT; NHR-260; NHR-270; NHRIC-17QAT; NHRIC-27QAT)

See individual housing specification sheets for more information.

LABELS AND LISTINGS


* cULus Listed for Damp Location when used with compatible housing



PRODUCT IMAGES & DIMENSIONS



NT-30D



3-7/8"

7-5/8"

6" BR/PAR30 Metal Splay Trim

Catalog No. _____

NT-30D = 6" Metal Splay Trim, White Finish

Compatible Housings

Catalog No. _____

NH-260 = Non-IC New Construction / 75W max

NH-270 = Shallow Non-IC New Construction / 75W max

NHIC-17/100DWQA = IC Double Wall Air-Tight New Const. / 75W max

NHIC-17QAT = IC Air-Tight New Construction / 75W max

NHIC-27QAT = Shallow IC Air-Tight New Construction / 75W max

NHR-260 = Non-IC Remodel / 75W max

NHR-270 = Shallow Non-IC Remodel / 75W max

NHRIC-17QAT = Shallow IC Air-Tight Remodel / 75W max

NHRIC-27QAT = Shallow IC Air-Tight Remodel / 75W max

Example: **NT-30D** = 6" BR/PAR30 Metal Splay Trim, White finish