

NT-5001

5" Baffle Splay Trim with Flange

Type _____

Project _____

Catalog No. _____

Notes _____

FEATURES

Trim: Precision spun high grade reflector and baffle with deep grooves to reduce aperture glare.

Mounting: Trim includes two "V" torsion springs to mount trim securely to housing. Replacement "V" torsion springs are available (NRA-86). Remove socket from plate within housing (if applicable), and mount socket in trim's neck.

COMPATIBLE HOUSINGS

Compatible with Line Voltage housings. See individual specification sheets for more information.

LAMP

75W BR30/PAR30 (NHIC-5010AT; NHRIC-5040AT; NFBIC-5INCATA)

LABELS AND LISTINGS

cULus Listed for Damp Locations when used with compatible housing



PRODUCT IMAGES AND DIMENSIONS




NT-5001B



NT-5001N



NT-5001W



5" Baffle Splay Trim with Flange

Catalog No. _____

NT-5001B = Black Aluminum Baffle with White Flange

NT-5001N = Natural Metal Aluminum Baffle Splay with Natural Metal Flange

NT-5001W = White Aluminum Baffle Splay with White Flange

Compatible Housings

Housing Type _____

NHIC-5010AT = 5" IC Air-Tight New Construction / 75W max

NHRIC-5040AT = 5" IC Air-Tight Remodel / 75W max

NFBIC-5INCATA = 5" IC Air-Tight Fire Rated New Construction / 75W max

Example: **NT-5001B** = Black Aluminum Baffle with White Flange