

# NT-5002

## 5" Air Tight Shallow Cone Reflector with Flange

Type \_\_\_\_\_

Project \_\_\_\_\_

Catalog No. \_\_\_\_\_

Notes \_\_\_\_\_

### FEATURES

**Trim:** Precision spun high grade reflector and baffle with deep grooves to reduce aperture glare.

**Mounting:** Trim includes two "V" torsion springs to mount trim securely to housing. Replacement "V" torsion springs are available (NRA-86). Remove socket from plate within housing (if applicable), and mount socket in trim's neck.

### COMPATIBLE HOUSINGS

Compatible with Line Voltage housings. See individual specification sheets for more information.

### LAMP


35W PAR30 maximum (NHIC-527QAT; NHRIC-527QAT; NFBIC-5INCATA )

### LABELS AND LISTINGS

cULus Listed for Wet Location when used with compatible housing



### PRODUCT IMAGES AND DIMENSIONS



### 5" Air-Tight Shallow Cone Reflector with Flange

Catalog No. \_\_\_\_\_

**NT-5002HZ** = Haze Air-Tight Shallow Cone Reflector with White Flange

### Compatible Housings

Catalog No. \_\_\_\_\_

**NHIC-527QAT** = Shallow IC Air-Tight New Construction / 35W max

**NHRIC-527QAT** = Shallow IC Air-Tight Remodel / 35W max

**NFBIC-5INCATA** = IC Air-Tight New Construction / 35W max

Example: **NT-5002HZ** = Haze Air-Tight Shallow Cone Reflector with White Flange