

NT-5010

5" Stepped Baffle with Metal Ring and Bracket

Type _____

Project _____

Catalog No. _____

Notes _____

FEATURES

Trim: Precision spun 0.040 aluminum baffle insert with deep grooves to reduce aperture glare. Non-reflective painted finishes. Trim may also be used with custom combination of ring finishes. Bracket includes two socket positions for optimum light control and output.

Mounting: Trim includes two "V" torsion springs to mount trim securely to housing. Replacement "V" torsion springs are available (NRA-86).

COMPATIBLE HOUSINGS

Compatible with Line Voltage housings. See individual specification sheets for more information.

LAMP

50W BR30/PAR30 Maximum (NHIC-501QAT; NHRIC-504QAT)


75W BR30/PAR30 Maximum (NFBIC-5INCATA)

LABELS AND LISTINGS

cULus Listed for Damp Locations when used with compatible housing



PRODUCT IMAGES AND DIMENSIONS



5" Stepped Baffle with Metal Ring and Bracket

Catalog No. _____

NT-5010B = Black Stepped Baffle with White Metal Ring and Bracket

Compatible Housings

Housing Type _____

NHIC-501QAT = 5" IC Air-Tight New Construction / 50W max

NHRIC-504QAT = 5" IC Air-Tight Remodel / 50W max

NFBIC-5INCATA = 5" IC Air-Tight New Construction / 75W max

Example: **NT-5010B** = Black Stepped Baffle with White Metal Ring and Bracket