

NT-5014

5" Air-Tight Cone Reflector with Metal Ring

Type _____

Project _____

Catalog No. _____

Notes _____

FEATURES

Trim: Precision spun 0.050 high grade reflector and metal trim ring may also be used with custom combination of ring finishes.

Mounting: Trim includes two "V" torsion springs to mount trim securely to housing. Replacement "V" torsion springs are available (NRA-86). Remove socket from socket plate within housing (if applicable) and mount socket on bracket (if applicable), and mount directly onto trim.

COMPATIBLE HOUSINGS

Compatible with Line Voltage housings. See individual specification sheets for more information.

LAMP

75W BR30/PAR30 (NHIC-5010AT; NHRIC-5040AT)

LABELS AND LISTINGS

cULus Listed for Damp Locations when used with compatible housing



PRODUCT IMAGES AND DIMENSIONS



NT-5014C




NT-5014HZ



NT-5014N



NT-5014W



5" Air-Tight Cone Reflector with Metal Ring

Catalog No. _____

- NT-5014C** = Specular Clear Air-Tight Cone Reflector with White Metal Ring
- NT-5014HZ** = Haze Air-Tight Cone Reflector with White Metal Ring
- NT-5014N** = Natural Metal Reflector with Natural Metal Ring
- NT-5014W** = Specular White Air-Tight Cone Reflector with White Metal Ring

Compatible Housings

Housing Type _____

- NHIC-5010AT** = 5" IC Air-Tight New Construction Housing / 75W max
- NHRIC-5040AT** = 5" IC Air-Tight Remodel Housing / 75W max

Example: **NT-5014W** = Specular White Air-Tight Cone Reflector with White Metal Ring