

# NT-5020

## 5" Specular Reflector with White Metal Ring

Type \_\_\_\_\_

Project \_\_\_\_\_

Catalog No. \_\_\_\_\_

Notes \_\_\_\_\_

### FEATURES

**Trim:** Precision spun high grade reflector and baffle with deep grooves to reduce aperture glare.

**Mounting:** Trim includes two "V" torsion springs to mount trim securely to housing. Replacement "V" torsion springs are available (NRA-86).

### COMPATIBLE HOUSINGS

Compatible with Line Voltage housings. See individual specification sheets for more information.

### LAMP

75W BR/PAR30 Maximum (NFBIC-5INCATA; NHIC-501QAT; NHRIC-504QAT)

### LABELS AND LISTINGS

cULus Listed for Damp Locations when used with compatible housing




### PRODUCT IMAGES AND DIMENSIONS



**NT-5020C**



**NT-5020W**



## 5" Specular Reflector with White Metal Ring

Catalog No. \_\_\_\_\_

**NT-5020C** = Specular Clear Reflector with White Metal Ring

**NT-5020W** = Specular White Reflector with White Metal Ring

## Compatible Housings

Housing Type \_\_\_\_\_

**NHIC-501QAT** = 5" IC Air-Tight New Construction / 75W max

**NHRIC-504QAT** = 5" IC Air-Tight Remodel / 75W max

**NFBIC-5INCATA** = 5" IC Air-Tight Fire Rated New Construction / 75W max

Example: **NT-5020W** = 5" Specular White Reflector with White Metal Ring