

# NT-5045

## 5" Wall Wash Eyelid with Baffle

Type \_\_\_\_\_

Project \_\_\_\_\_

Catalog No. \_\_\_\_\_

Notes \_\_\_\_\_

### FEATURES

**Trim:** Precision spun 0.040 aluminum baffle with deep grooves to reduce aperture glare and white flange with steel half moon face.

**Mounting:** Trim includes two "V" torsion springs to mount trim securely to housing. Replacement "V" torsion springs are available (NRA-86).

### COMPATIBLE HOUSINGS

Compatible with Line Voltage housings. See individual specification sheets for more information.

### LAMP


75W BR30/PAR30 (NHIC-5010AT; NHRIC-5040AT)

### LABELS AND LISTINGS

cULus Listed for Damp Locations when used with compatible housing



### PRODUCT IMAGES AND DIMENSIONS



## 5" Wall Wash Eyelid with Baffle

Catalog No. \_\_\_\_\_

**NT-5045W** = White Wall Wash Eyelid with White Baffle and White Flange

## Compatible Housings

Catalog No. \_\_\_\_\_

**NHIC-5010AT** = 5" IC Air-Tight New Construction Housing / 75W max

**NHRIC-5040AT** = 5" IC Air-Tight Remodel Housing / 75W max

Example: **NT-5045W** = 5" White Wall Wash Eyelid with White Baffle and White Flange