

# NT-5060

## 5" PAR30 Gimbal Ring with Metal Trim

Type \_\_\_\_\_

Project \_\_\_\_\_

Catalog No. \_\_\_\_\_

Notes \_\_\_\_\_

### FEATURES

**Trim:** Adjustable metal gimbal ring can be adjusted up to 28° with a short neck, and 19° with a long neck.

**Mounting:** Trim includes two "V" torsion springs to mount trim securely to housing. Replacement "V" torsion springs are available (NRA-86). Remove socket from socket plate within housing (if applicable), and mount directly onto trim.

### COMPATIBLE HOUSINGS

Compatible with Line Voltage housings. See individual specification sheets for more information.

### LAMP

50W PAR30 Maximum (NHIC-501QAT; NHRIC-504QAT)

75W PAR30 Maximum (NFBIC-5INCATA)

### LABELS AND LISTINGS

cULus Listed for Damp Locations when used with compatible housing




### PRODUCT IMAGES AND DIMENSIONS



**NT-5060BZ**



**NT-5060W**



## 5" PAR30 Gimbal Ring with Metal Trim

Catalog No. \_\_\_\_\_

**NT-5060BZ** = Bronze Metal Trim with Gimbal Ring

**NT-5060W** = White Metal Trim with Gimbal Ring

## Compatible Housings

Catalog No. \_\_\_\_\_

**NHIC-501QAT** = 5" IC Air-Tight New Construction Housing / 50W max

**NHRIC-504QAT** = 5" IC Air-Tight Remodel Housing / 50W max

**NFBIC-5INCATA** = 5" Line Voltage IC Air-Tight Fire Rated Housing / 75W max

Example: **NT-5060W** = White Metal Trim with Gimbal Ring