# PRODUCT DESCRIPTION

Line voltage rear loading track head with yoke that provides full adjustment of light source for special aiming and has single tightening knobs assure secure lock on angle position.

### FEATURES

- · Die cast aluminum provies superior strength and rigidity.
- · One or two circuit track capable.
- · Accepts LED lamps

#### CONSTRUCTION

Housing: 0.030" Deep drawn steel construction with simple, yet decorative design. All edges are softened for aesthetic appearance

Yoke: 0.085" Rigid steel "wishbone" yoke connects fixture housing to electrical contact head. Single plastic angle tightening knobs maintain clean, decorative appearance of the fixture and provides secure angle position

### ELECTRICAL

Voltage: 120V input Socket: Medium base Lamp: 50W PAR20 max. (not included)

Finishes: Black, Bronze, Natural Metal, or White heat rated baked enamel paint. Custom painting or anodizing for special applications are also available. Custom finishes will require lead times that vary depending on vendor schedule. Please consult factory for quotation, and provide either a Dunn Edwards number or color chip for exact matching.

## **ONE/TWO CIRCUIT CONVERSION**

Positive contact (opposite neutral and ground contacts) is preset to "down" position at factory but may be raised to the higher position to install onto the second circuit of Nora Lighting NT- 2300 series two-circuit track.

LABELS AND LISTINGS UL Listed





Catalog No.

Type

#### Notes







NTH-112B/A

NTH-112BZ





NTH-112N

**NTH-112W** 



#### **PAR20 Rear Loading Gimbal Ring**

Catalog No.	Finish	Adapter
NTH-112	B/A = Black	(blank) = H-style
	BZ = Bronze	/J = J-style
	N = Natural Metal	/L = L-style
	W = White	

Example: NTH-112B/A = PAR20 Rear Loading Gimbal Ring, Black, H-Style

N G