

# NTLE-875

## 4' Track Pack with (3) MAC XL LED Track Heads

Source: 18W LED per head

Up to 1250lm per head

Type

Project

Catalog No.

Notes

### PRODUCT DESCRIPTION

Track pack comes complete and ready to install with mounting hardware and track heads. Components includes: (1) 4' single circuit track, (2) end caps, (1) floating canopy feed and (3) MAC XL LED track heads. The utilitarian style fits almost any design criteria.

### FEATURES

- Over 75% energy savings when compared to incandescent
- 4' Track Pack includes all hardware and ready to install
- Black, silver or White finish
- Up to 1250lm / 18W LED output per head
- Field adjustable beam spreads (Flood installed and spot included)
- 2700K, 3000K, 3500K or 4000K @ 90 CRI
- Dimmable
- Easily to longer lengths or additional track heads
- 5-Year Limited Warranty

### CONSTRUCTION

**Housing:** Die-cast aluminum construction dissipates heat for longer life.

**Adjustability:** 350° horizontal and 90° vertical adjustment

### ELECTRICAL

**Input Voltage:** 120V

**Lumens / Wattage Per Head:** Up to 1250lm / 18W

**Color Temperature:** 2700K 3000K, 3500K or 4000K

**Color Rendering Index:** 90+ CRI

**Beam Spread:** 56° Flood installed and 24° spot included

**Lifetime:** 44,000 hours @ L70

**Dimming:** ELV

[Click Here](#) or check complete dimmer list at [www.NoraLighting.com](http://www.NoraLighting.com) in the "Compatibility" page under "Resources" tab

**One / Two Circuit Conversion:** Positive contact (opposite neutral and ground contacts) is preset to "down" position at factory, but may be raised to the higher position to install onto the second circuit of Nora Lighting NT-2300 series two-circuit track.

### LABELS AND LISTINGS

- cULus Listed for dry locations
- ENERGY STAR certified
- [5-Year Limited Warranty](#)



Performance Data Per Head		
Part Number	Lumens	CCT
<b>NTLE-875927</b>	1069lm	2700K
<b>NTLE-875930</b>	1211lm	3000K
<b>NTLE-875935</b>	1232lm	3500K
<b>NTLE-875940</b>	1252lm	4000K

*Delivered lumens will vary depending on beam spread and finish*

### PRODUCT IMAGE



NTLE-875B



NTLE-875S



NTLE-875W

## 4' Track Pack with (3) MAC XL LED Track Heads

Series	Color Temperature	Finish
<b>NTLE-875</b> = 4' Track Pack with (3) MAC XL LED Track Heads	<b>927</b> = 2700K	<b>B</b> = Black
	<b>930</b> = 3000K	<b>S</b> = Silver
	<b>935</b> = 3500K	<b>W</b> = White
	<b>940</b> = 4000K	

Example: **NTLE-875927B** = 4' Track Pack with (3) MAC XL LED Track Heads, 2700K / 90 CRI, Black Finish


# PHOTOMETRICS

## MAC XL LED Track Head

Type \_\_\_\_\_  
 Project \_\_\_\_\_  
 Catalog No. \_\_\_\_\_  
 Notes \_\_\_\_\_

### Test Information

Test Number: NTR11020  
 Part Number: NTE-875L940X18W  
 Beam Spread: 25° Spot  
 Lumens: 1252lm  
 Wattage: 17W  
 Efficacy: 73lpw  
 CCT / CRI: 4000K / 90 CRI  
 Spacing Criteria (0°-180°): 0.44  
 Spacing Criteria (90°-270°): 0.44



### Illuminance at a Distance

Distance from Luminaire	FC at Nadir	Beam Diameter
4'	279fc	1'-10"
6'	124fc	2'-8"
8'	69.7fc	3'-7"
10'	44.6fc	4'-6"
12'	31fc	5'-5"

### Zonal Lumen Summary


Zone	Lumens	% Luminaire
0-30	1031	82.4
0-40	1127	90
0-60	1214	97
0-90	1242	99.2
90-180	9	0.8
0-180	1252	100

### Candela Table

Vertical Angles	Candela
0	4460
5	4037
15	1633
25	476
35	146
45	68

### Test Information

Test Number: NTR11021  
 Part Number: NTE-875L940X18W  
 Beam Spread: 48° Flood  
 Lumens: 1251lm  
 Wattage: 17.48W  
 Efficacy: 72lpw  
 CCT / CRI: 4000K / 90 CRI  
 Spacing Criteria (0°-180°): 0.76  
 Spacing Criteria (90°-270°): 0.76



### Illuminance at a Distance

Distance from Luminaire	FC at Nadir	Beam Diameter
4'	105fc	3'-6"
6'	46.7fc	5'-4"
8'	26.2fc	7'
10'	16.8fc	8'-10"
12'	11.7fc	10'-7"

### Zonal Lumen Summary

Zone	Lumens	% Luminaire
0-30	862	68.9
0-40	1067	85.3
0-60	1209	96.6
0-90	1246	99.6
90-180	5	0.4
0-180	1251	100

### Candela Table

Vertical Angles	Candela
0	1680
5	1636
15	1306
25	769
35	321
45	124

### Lumen Output Multipliers

Color Temperature: 2700K (0.84), 3000K (0.95), 4000K (1.00)