

NTS-31 / NTS-32 / NTS-33

6" BR/PAR30 Reflector

Type	
Project	
Catalog No.	
Notes	

CONSTRUCTION

Precision spun 0.050 aluminum high grade reflector. Separate trim ring available in plastic or metal, may also be used with custom combination of ring finishes.

MOUNTING

Trim includes two coil springs that clip and securely hold the trim into the housing when installed. Replacement coil springs are available (NRA-22).

COMPATIBLE LAMP(S) / HOUSINGS

Line Voltage:

75W R/PAR30 max. (NH-260; NH-270; NHIC-170AT; NHIC-17/100DWQA; NHIC-270AT; NHR-260; NHR-270; NHRIC-170AT; NHRIC-270AT)

LISTINGS

cULus Listed for Damp Location when used with compatible housing



PRODUCT IMAGES AND DIMENSIONS



NTS-31




NTS-31C



NTS-31HZ



NTS-33



6" BR/PAR30 Reflector

Catalog No.

- NTS-31 = 6" Specular Clear Reflector with White Plastic Ring
- NTS-31C = 6" Specular Clear Reflector with Chrome Plastic Ring
- NTS-31HZ = 6" Haze Reflector with White Plastic Ring
- NTS-33 = 6" Specular White Reflector with White Plastic Ring

Compatible Housings

Catalog No.

- NH-260 = Non-IC New Construction / 75W Max.
- NH-270 = Non-IC Shallow New Construction / 75W Max.
- NHIC-17/100DWQA = ICAT Double Wall New Construction / 75W Max.
- NHIC-170AT = ICAT New Construction / 75W Max.
- NHIC-270AT = ICAT Shallow New Construction / 75W Max.
- NHR-260 = Non-IC Remodel / 75W Max.
- NHR-270 = Non-IC Shallow Remodel / 75W Max.
- NHRIC-170AT = ICAT Remodel / 75W Max.
- NHRIC-270AT = ICAT Shallow Remodel / 75W Max.

Example: NTS-31 = 6" Specular Clear Reflector with White Plastic Ring