

Project:	Туре:
Prepared By:	Date:

# **Technical Specifications**

#### **Performance**

# **Product Type:**

A-line Contractor Series

#### Description:

Economical contractor grade A-lamps in convenient pack sizes that eliminate excess waste at the right price.

## Wattage Equivalency:

60W Incandescent

### Input Wattage:

10W

## Lumens (Nominal):

800lm

#### Efficacy:

80lm/W

#### L70 Lifespan:

15,000-Hour LED lifespan based on IES LM-70 results

## **Electrical**

# THD:

≤20%

### **Power Factor:**

>0.7

### Dimmable:

Yes

## Dimming Type:

See Dimmer Compatibility List

#### Input Voltage:

120V

#### **Operating Frequency:**

60 Hz

# Input Current @ 120V (mA):

101mA

## **Operating Temperature:**

-4°F to 113°F (-20°C to 45°C)

# Optical

## Beam Angle:

23Uo

# **LED Characteristics**

# Color Temperature:

3000K

## Color Accuracy (CRI):

≥80 CRI

## **Color Consistency:**

<7-step MacAdam Ellipse binning to achieve consistent fixture-to-fixture color

#### Construction

### Base Type:

E26 Edison

## Finish:

White

# Bulb Shape:

A19

#### **Endcap Material:**

Aluminum

### **Enclosure Material:**

Plastic

## Lens Finish:

Frosted

# Compliance

### Listings:

UL Listed

# **Environment:**

Suitable for use in dry and damp environments

# A19-10-E26-830-DIM 6PK



# **Technical Specifications (continued)**

#### **Fixture Rating:**

Suitable for use in enclosed fixtures

#### **Energy Star Approved:**

This product is ENERGY STAR® Version 2.2 Certified

## **Energy Star ID:**

2357501

## **Model Number for Certification:**

A10086(A19-10-E26-830-DIM)

#### T20 Compliant:

Not Compliant

#### California Title 24 JA8 Compliant:

Not Compliant

## California Energy Commission (CEC) Status:

Not Lawful for Sales in California

#### RoHS:

Mercury and UV free. RoHS-compliant components.

#### FCC:

Complies with Part 15B of the FCC Rules

#### Other

# Warranty:

RAB warrants that our LED products will be free from defects in materials and workmanship for a period of three (3) years from the date of delivery to the end user, including coverage of light output, color stability, driver performance and fixture finish. RAB's warranty is subject to all terms and conditions found at rablighting.com/warranty.

## Note:


All values are typical (tolerance +/- 10%)

## **Buy American Act Compliance:**

RAB values USA manufacturing! Upon request, RAB may be able to manufacture this product to be compliant with the Buy American Act (BAA). Please contact customer service to request a quote for the product to be made BAA compliant.

# **Case and Pallet Dimensions**

	QTY	LENGTH (in)	WIDTH (in)	HEIGHT (in)
CASE	24	13.58	9.45	5
PALLET	2	42.13	39.37	42.52



# **Features**

Energy efficient replacement for incandescent and halogen lamps

Constructed from durable plastic which lowers risk of breakage

Rated for use in open fixtures in dry or damp locations

Frosted lens produces smooth diffuse light

6-pack makes it convenient for contractors

# **Ordering Matrix**

Family		Wattage		Base Type		CRI/Color Temp	Dimmable	Pack	Voltage
A19	-	10	-	E26	-	830	DIM	6PK	
	<b>8.5</b> = 8.5W <b>10</b> = 10W <b>13.5</b> = 13.5W		<b>E26</b> = E26 Base		<b>850</b> = 80 CRI, 5000K <b>840</b> = 80 CRI, 4000K <b>830</b> = 80 CRI, 3000K	ND = Non-Dimmable DIM = Dimmable	<b>6PK</b> = 6 Pack	<b>Blank</b> = 120V	