



|                     |              |
|---------------------|--------------|
| <b>Project:</b>     | <b>Type:</b> |
| <b>Prepared By:</b> | <b>Date:</b> |

| Driver Info |                  | LED Info       |                |
|-------------|------------------|----------------|----------------|
| Type        | Constant Current | Watts          | 90/78W         |
| 120V        | 1.25A            | Color Temp     | Amber          |
| 208V        | 0.73A            | Color Accuracy | N/A            |
| 240V        | 0.63A            | L70 Lifespan   | 100,000 Hours  |
| 277V        | 0.55A            | Lumens         | 6,773/6,022 lm |
| Input Watts | 90.2/73.9W       | Efficacy       | 75.1/81.5 lm/W |

## Technical Specifications

### Field Adjustability

#### Field Adjustable (Wattage):

Field adjustable light output in 2 discrete steps:  
Medium Housing: 90W/78W (factory default 90W)

### Compliance

#### UL Listed:

Suitable for wet locations

### IP Rating:

Ingress protection rating of IP66 for dust and water

### LED Characteristics

#### LEDs:

Long-life, high-efficacy, discrete, surface-mount LEDs

### Electrical

#### Driver:

78W: Constant Current, Class 2, 120-277V, 50/60 Hz,  
120V: 0.65A, 208V: 0.38A, 240V: 0.33A, 277V: 0.29A

90W: Constant Current, Class 2, 120-277V, 50/60 Hz,  
120V: 0.75A, 208V: 0.44A, 240V: 0.38A, 277V: 0.33A

150W: Constant Current, Non-Class 2, 120-277V,  
50/60 Hz, 120V: 1.25A, 208V: 0.73A, 240V: 0.63A,  
277V: 0.55A

### Dimming Driver:

Driver includes dimming control wiring for 0-10V dimming systems. Requires separate 0-10V DC dimming circuit. Dims down to 10%.

### THD:

5.65% at 120V, 12.17% at 277V

### Power Factor:

99.8% at 120V, 90% at 277V

### Surge Protection:

Line to Line: 10kV  
Line to Ground: 6kV

### Performance

#### Lifespan:

100,000-Hour LED lifespan based on IES LM-80 results and TM-21 calculations

### Wattage Equivalency:

Equivalent to 400W Metal Halide

### Construction

#### IES Classification:

The Type II distribution is meant for lighting large areas, located by the roadside. Typically found on wide walkways, on ramps, entrance roadways and bike paths.

### Cold Weather Starting:

The minimum starting temperature is -40°C (-40°F)

### Ambient Temperature :

Max Power Temp Rating: 40°C (104°F)  
Middle Power Temp Rating: 52°C (125°F)  
Low Power Temp Rating: 54°C (130°F)

### Housing:

Die-cast aluminum

### Mounting:

2 3/8" slipfitter mount with stainless steel hardware

### Tilt Increment:

Rotates in 5 degree increments

### Lens:

Polycarbonate lens

### Reflector:

Aluminum reflector with white polycarbonate

### Vibration Rating:

3G vibration rating per ANSI C136.31

### Effective Projected Area:

EPA = 0.44

**Technical Specifications (continued)**

**Gaskets:**

High-temperature silicone gaskets

**Finish:**

Formulated for high durability and long-lasting color

**Green Technology:**

Mercury and UV free. RoHS-compliant components.

**Optical**

**BUG Rating:**

BUG Rating 60W: B3 U0 G2

BUG Rating 90W: B3 U0 G1

Bug Rating 78W: B3 U0 G1

**Other**


**Warranty:**

RAB warrants that our LED products will be free from defects in materials and workmanship for a period of ten (10) years from the date of delivery to the end user, including coverage of light output, color stability, driver performance and fixture finish. RAB's warranty is subject to all terms and conditions found at [rablighting.com/warranty](http://rablighting.com/warranty).

**Buy American Act Compliance:**

RAB values USA manufacturing! Upon request, RAB may be able to manufacture this product to be compliant with the Buy American Act (BAA). Please contact customer service to request a quote for the product to be made BAA compliant.

**Dimensions**



**Features**

- Wildlife-friendly amber light
- 0-10V dimmable standard
- IP66 Rated
- 100,000-Hour LED lifespan
- 10-Year, No-Compromise Warranty

## Ordering Matrix

| Family | Housing Size  | Distribution   | Mounting  | Wavelength        | Finish  | Voltage  | Options  |
|--------|---|--|---|-------------------|---|--|--|
| ALED   | M   | 2T   | SF  | YA                | W   |  |  |
|        | <b>S</b> = Small (60W/40W)<br><b>M</b> = Medium (90W/78W) | <b>2T</b> = Type II <sup>1</sup><br><b>3T</b> = Type III<br><b>4T</b> = Type IV <sup>1</sup><br><b>5T</b> = Type V<br><b>AT</b> = Auto Dealership Optic <sup>1</sup> | <b>Blank</b> = Universal Pole Mount<br><b>SF</b> = Slipfitter<br><b>WM</b> = Wall Mount | <b>YA</b> = Amber | <b>Blank</b> = Bronze<br><b>W</b> = White <sup>1</sup><br><b>B</b> = Black <sup>1</sup> | <b>Blank</b> = 120-277V, 0-10V Dimming<br><b>/480</b> = 480V, 0-10V Dimming <sup>2</sup> | <b>/7PR</b> = 7 Pin Twistlock Receptacle<br><b>Blank</b> = No Option |

<sup>1</sup> Special order.

<sup>2</sup> 480V is only available in ALED Medium.